



0340

Protector

Cube Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Built-in, spring loaded pull handle**
- **Large 2-person fold down handles**
- **Stainless steel caster wheels included**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Easy open Double Throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



0340
Standard



0344
With Padded Dividers



0340NF
No Foam



0340WF
With Foam

DIMENSIONS

Interior (L×W×D)	18.00 x 18.00" x 18.00 (45.7 x 45.7 x 45.7 cm)
Exterior (L×W×D)	20.50 x 20.50" x 19.25 (52.1 x 52.1 x 48.9 cm)
Lid Depth	4.50" (11.4 cm)
Bottom Depth	13.50" (34.3 cm)
Total Depth	18" (45.7 cm)
Int Volume	3.38 ft³ (0.096 m³)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

 Black	 Desert Tan	 OD Green
-----------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------

WEIGHT

Weight With Foam	29.76 lbs (13.5 kg)
Weight Empty	24.00 lbs (10.9 kg)
Buoyancy	220.46 lbs (100 kg)
Master Pack Weight	32.24 lbs (14.6 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67
Def Stan 81-41
STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid)	1.00" Pad
Layer 2 (Lid)	3.00" Convolute
Layer 3 (Base)	1.00" Pad
Layer 4 (Base)	1.00" Pad
Layer 5 (Base)	3.84" Pick N Pluck
Layer 6 (Base)	3.84" Pick N Pluck
Layer 7 (Base)	3.84" Pick N Pluck

OTHER

Wheels	2
Master Pack	1
Nameplate	yes
Reduced Area	yes
Military	yes

ACCESSORIES



0341
7 pc. Replacement Foam Set



0343
Replacement O-ring



0345
Padded Divider Set



0349
Lid Organizer



0357
Cube Case Mobility Package



1507

Quick Mounts - set of 4
