

Model 210 Heated Recirculator



Model 210

Key Specifications

Description	Heated Recirculator
Working Temperature Range °C	Ambient to 70°
Temperature Stability °C	±0.2°
Pump Type	Centrifugal

Key Features

IMMERSION CIRCULATOR & OPEN TANKS

Key Features

- Large, universal icon and English display
- On-screen prompts
- Single-point calibration capability

Common Specifications

Working Temperature Range °F	Ambient to 158°
Working Temperature Range °C	Ambient to 70°
Temperature Stability °F	±0.4°
Temperature Stability °C	±0.2°
Pump Type	Centrifugal
Pump Speed	Single

Process Connections	1/2" barb fitting
Over-Temperature Protection / Failsafe Heater Control	Yes
Low Liquid Level Protection	Yes
Maximum Ambient Temperature °F	95°
Maximum Ambient Temperature °C	35°
Overall Dimensions (L x W x H) (inches)	8 x 9.5 x 8 in
Overall Dimensions (L x W x H) (cm)	20.3 x 24.1 x 20.3 cm
Shipping Weight (pounds)	12.0
Shipping Weight (kilograms)	5.4
Catalog Page Number	67

60 Hz Only

Part Number	40300
Maximum Pressure (psi)	2.0
Maximum Pressure (bar)	0.13
Maximum Pressure Flow Rate (gpm)	3.00
Maximum Pressure Flow Rate (l/min)	11.4
Included Hardware	Tubing and clamps
Heater Wattage	750

50 Hz Only

Part Number	40301
Maximum Pressure (psi)	2.0
Maximum Pressure (bar)	0.13
Maximum Pressure Flow Rate (gpm)	3.00
Maximum Pressure Flow Rate (l/min)	11.4
Included Hardware	Tubing and clamps
Heater Wattage	750
Regulatory Approvals	CE