

# CO<sub>2</sub> measuring instrument

testo 535 – Digital CO<sub>2</sub> measuring instrument with App connection

---

Simple, fast and precise measurement of CO<sub>2</sub> concentration

---

Audible alarm sounds if a limit value is exceeded

---

Fast in-app configuration, graph history, second screen and measurement data memory in the testo Smart App

---

High accuracy of measurement results due to long-term stable infrared sensor technology

---

Timed and point mean value calculation

---



For **indoor air quality and comfort**, the measurement of the carbon dioxide content in the room air is crucial. To obtain precise results quickly, you need a suitable measuring instrument.

The compact CO<sub>2</sub> measuring instrument testo 535 with practical App connection allows you to carry out this important measurement easily and efficiently - and thus ensure comfort and a healthy indoor climate.

Thanks to the long-term stable infrared sensor technology,

the measured values are repeatable and comparable even over longer periods of time. Ideal for recurring comparative measurements. Here, you are also supported by the time and point averaging directly in the measuring instrument.


By the way, the testo Smart App displays the measured values as a table or graph, stores the results and documents them. This not only makes it easy to configure the measuring instrument individually - the App also turns your smartphone into a second display!

## Ordering data / technical data / accessories

### testo 535

testo 535, CO<sub>2</sub> measuring instrument with App connection, audible alarm, incl. transport bag, calibration protocol and 3 x AA batteries

Order no. 0563 0535 01



#### The testo Smart App

- Simple and fast: Measurement menus for numerous applications provide optimum support in configuring and carrying out the measurement
- Clear graphical presentation of readings, e.g. as a table, for quick interpretation of results
- Create digital measurement reports including photos as PDF/CSV files on site and send via e-mail



Free download  
for Android and iOS



Sensor type	CO <sub>2</sub> sensor
Measuring range	0 to 10,000 ppm
Accuracy ±1 digit	±(50 ppm + 5 % of mv) (0 to 2,500 ppm) ±(100 ppm + 5 % of mv) (2,501 to 10,000 ppm)
Solution	1 ppm
General technical data	
Operating temperature	32° to 122 °F
Storage temperature	32° to 122 °F
Battery type	3 x AA
Battery life	30 h
Dimensions	9.0 x 2.4 x 1.1 in
Weight	0.50 lbs.
Protection class	Measuring instrument: IP 40 Probe: IP20
Housing material	ABS + PC / TPE

Accessories	Order no.
testo Bluetooth® printer, incl. 1 roll of thermal paper, rech. battery and power supply	0554 0621
Spare thermal paper for printer (6 rolls), measurement data documentation can be read for up to 10 years	0554 0568
ISO CO <sub>2</sub> calibration certificate; CO <sub>2</sub> probes; calibration points 0; 1000; 5000 ppm	0520 0033

1981 2264/msp/09.2022

Subject to change, including technical modifications.