
testo 174T / testo 174H

0572 1740 01 / 0572 1741 01


1




2




3



4



5



6



testo ComSoft BASIC

testo ComSoft PROF



	°C					g	
60 x 38 x 19 mm 2.4 x 1.5 x 0.7 in	testo 174T: -30 ... +70 °C -22 ... +158 °F testo 174H: -20 ... +70 °C -4 ... +158 °F -40 ... +70 °C -40 ... +158 °F	2x 3 V (CR 2032 Lithium) testo 174T: 500 days (15 min meas. cycle, +25 °C / 77 °F) testo 174H: 1 year (15 min meas. cycle, +25 °C / 77 °F)	testo 174T: 0.1 °C 0.1 °F testo 174H: 0.1 °C 0.1 °F 0.1 % RH	testo 174T: -30 ... +70 °C -22 ... +158 °F testo 174H: -20 ... +70 °C -4 ... +158 °F 0 ... 100 % RH	testo 174T: ± 0.5 °C (-30 ... +70 °C) ± 0.5 °F (-22 ... +158 °F) testo 174H: ± 0.5 °C (-20 ... +70 °C) ± 0.5 °F (4 ... +158 °F) ±3 % RH (2 % RH ... 98 % RH) @ 25 °C ± 0.03 % RH/K ± 1 digit	35 g 1.2 oz	testo 174T: IP 65 testo 174H: IP 20

1.888.610.7664 www.calcert.com sales@calcert.com

Approval and Certification

Product	testo 174T testo 174H
Model	0572 1740 0572 1741
Mat.-No.	0572 1740 01 0572 1741 01
Date	20.10.2025

The use of the wireless module is subject to the regulations and stipulations of the respective country of use, and the module may only be used in countries for which a country certification has been granted. The user and every owner has the obligation to adhere to these regulations and prerequisites for use, and acknowledges that the re-sale, export, import etc. in particular in countries without wireless permits, is his responsibility.

Country	Comments
Argentina	Approved
Australia & New Zealand	E 1561 80007249603
Brazil	Approved
Canada	See IC Warnings
Chile	Approved
China	Approved
Europa + EFTA	CE Hereby, Testo SE & Co. KGaA declares that the radio equipment types testo 174T (0572 1740) and testo 174H (0572 1741) are in compliance with Directive 2014/30/EU. The full text of the EU declaration of conformity is available at the following internet address: **EU countries:** Belgium (BE), Bulgaria (BG), Denmark (DK), Germany (DE), Estonia (EE), Finland (FI), France (FR), Greece (GR), Ireland (IE), Italy (IT), Latvia (LV), Lithuania (LT), Luxembourg (LU), Malta (MT), Netherlands (NL), Austria (AT), Poland (PL), Portugal (PT), Romania (RO), Sweden (SE), Slovakia (SK), Slovenia (SI), Spain (ES), Czech Republic (CZ), Hungary (HU), Republic of Cyprus (CY). **EFTA countries:** Iceland, Liechtenstein, Norway, Switzerland WEEE Reg. no.: DE 75334352
India	Approved
Japan	Approved
Jordan	Approved
Malaysia	Approved
Philippines	Approved
South Africa	Approved
South Korea	Approved
Thailand	Approved
Türkiye	Approved
United Arab Emirates	Approved
United Kingdom (UK)	UKCA The UK Declaration of Conformity can be found on the testo homepage.
USA	See FCC Warnings

	Comments
Hongkong	Approved
Taiwan	Approved
NSF	For testo 174T: NSF
EN12830	For testo 174T: Acc. to EN12830-S, T, 0.5 Ia

IC Warnings

CAN ICES-003(B) / NMB-003(B)
This Class B digital apparatus complies with Canadian ICES-003.

Co-Location
This device must not be co-located or operated in conjunction with any other antenna or transmitter.

FCC Warnings

Information from the FCC (Federal Communications Commission)

For your own safety
Shielded cables should be used for a composite interface. This is to ensure continued protection against radio frequency interference.

FCC warning statement
This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be deter-mined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution
Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Warning
This device complies with Part 15 of the FCC Rules.

Operation is subject to the following two conditions:

(1) this device may not cause harmful interference, and

(2) this device must accept any interference received, including interference that may cause undesired operation.

Co-Location
This device must not be co-located or operated in conjunction with any other antenna or transmitter.

Manufacturer/ importer

Testo SE & Co. KGaA

Warning: Please follow the instructions when using the product.

1.888.610.7664 www.calcert.com sales@calcert.com