



| Item | Description | Minimum Circumference | Maximum Circumference | Width |
|--------|--|-----------------------|-----------------------|--------|
| 09200 | Wristband only, Red, White and Blue | 5.75 in. | 13 in. | 0.630" |
| 09041 | Wristband only, Black | 5.75 in. | 13 in. | 0.630" |
| 09220 | Wristband only, White | 5.75 in. | 13 in. | 0.630" |
| *09230 | Wristband only, White | 5.75 in. | 13 in. | 0.630" |
| 09042 | Wristband only, X-large, Black | 6.25 in. | 14.5 in. | 0.630" |
| 09085 | Wrist Strap, Black, 6' coil cord | 5.75 in. | 13 in. | 0.630" |
| 91070 | Wrist Strap, Black, 6' cord & angle banana | 5.75 in. | 13 in. | 0.630" |
| 09221 | Wrist Strap, White, 6' coil cord | 5.75 in. | 13 in. | 0.630" |
| *09231 | Wrist Strap, White, 6' coil cord | 5.75 in. | 13 in. | 0.630" |
| 09222 | Wrist Strap, White, 10' coil cord | 5.75 in. | 13 in. | 0.630" |
| *09232 | Wrist Strap, White, 10' coil cord | 5.75 in. | 13 in. | 0.630" |

*Cleaned and Packaged in a Class 1000 Controlled Environment. Click

Meets ANSI/ESD S1.1 wristband resistance interior < 100 kilohms ($<1 \times 10^5$ ohms)

Meets ANSI/ESD S1.1 wristband resistance exterior >10 megohms ($>1 \times 10^7$ ohms)

Meets ANSI/ESD S20.20 and Wrist Strap standard ANSI/ESD S.1

Unless otherwise noted, tolerance $\pm 10\%$

Specifications and procedures subject to change without notice.

- A. ABS cap with slotted opening to allow size adjustment.
- B. 300 Series Stainless Steel Backplate forms channel to hold up to 10 links of band allowing size adjustment.
- C. 4mm snap stud machined from 300 series stainless steel. Fits to 4mm spring loaded medical type socket. Coil cord disengages from snap with 1-5 lbs. of perpendicular force.
- D. Inside links constructed of 300 Series Stainless Steel. Width of links is 0.630".
- E. .002" polyphenylsulfone sheet is laminated to each link. Provides >5,000 volt RMS insulation per ASTM D149. Scratch resistant.
- F. Size is adjusted by sliding 1 to 10 links of the band into the backplate "C" channel.
- G. 300 Series Stainless Steel clip for electrical contact between snap stud and backplate.
- H. Underwriters Laboratory listing 90P1C.



Made in the
United States of America

Premium Metal Expansion Wristband

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710
PHONE (909) 627-8178 FAX (909) 627-7449
DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER:
09041

DATE:
January 2016

© 2016 DESCO INDUSTRIES INC.
Employee Owned