

## IMT100 and IMT100X Industrial Multi Tester



- Bluetooth live streaming and data management
- Full colour graphic display
- DC voltage and polarity test
- AC voltage, phase rotation and frequency
- Insulation resistance and surface leakage current detection
- 4 wire low resistance bonding test
- 2 wire continuity and diode test
- Data storage and management
- CAT III 600 V up to 3000 m
- Multipurpose industrial carrycase
- Rechargeable batteries and charger

### DESCRIPTION

The IMT100 is a versatile handheld multi-testing instrument featuring dedicated three-wire insulation resistance and four-wire Kelvin low resistance capabilities, ideal for industrial applications. With over 13 test functions and the reliability of Megger technology, it supports effective continuity, bonding, and insulation resistance testing making it a reliable multi environment solution for photovoltaic and electric vehicle systems.

The IMT100 supports DC/AC voltage, insulation, low resistance, continuity, inductance, and capacitance testing, with built-in temperature measurement and compensation. It's housed in a rugged, IP54-rated over-moulded case and supplied in a versatile industrial carrycase for accessories and field tools

### FEATURES

- Full set of detachable test leads with interchangeable clips and probes for different applications, including PV connectors.
- Guided lead set up diagrams.
- Rechargeable batteries with mains charger kit.
- DC voltage with polarity test, and AC voltage with phase rotation and frequency.
- Unique resistance testing capabilities with two, three and four terminals, including a guard connection, to eliminate any surface leakage current
- Data storage for up to 256 tests, which can be downloaded to a USB.

- CertSuite LITE and BLE enable real-time testing and reporting with onboard storage and secure wireless connectivity.
- Meets IEC62446 for PV testing and additional tests.
- Meets UN EEC R100 Regulation for Electric Vehicle testing.
- Environmental protection to IP54, providing protection against moisture and dust ingress, including the battery and fuse compartment.
- Rubber over moulding housing combining a tough shock absorbing outer protection with excellent grip, on a strong modified ABS housing, providing a robust case.
- Multipurpose industrial carrycase.

### INDUSTRIES

- Photovoltaic installations: domestic, industrial, and utility scale
- Electric vehicles: manufacturing and workshops
- Power generation: infrastructure maintenance
- Rotating machinery, motors, and generators: manufacture and workshops
- Electrical installations: domestic, industrial, and production lines

### TYPICAL APPLICATIONS

- Testing and fault-finding during Installation, commissioning, start-up, and regular maintenance.

## IMT100 and IMT100X Industrial Multi Tester

- Photovoltaic installations (Domestic, Industrial, Utility scale): Insulation Resistance, Dielectric Absorption Ratio (DAR), Polarization Index (PI), Electrical Bonding verification, AC and DC voltage, temperature, and Diode testing.
- Electric Vehicles (HEV, PHEV, BEV): AC and DC voltage testing; Insulation Resistance, Continuity, and Low Resistance Bonding testing with 2, 3, and 4 test lead methods; Capacitance and Temperature measuring,
- Industrial and domestic installations: Frequency and TRMS AC voltage, DC voltage, Insulation Resistance, 3 phase rotation, Temperature, Capacitance, Inductance and Resistance measurement.
- Rotating machinery: Continuity, Low resistance, 3 phase Insulation Testing, Timed Insulation Testing, Dielectric Absorption Ratio (DAR), Polarization Index (PI), Temperature testing and compensation and Motor direction of rotation.

### SAFETY

The IMT100 is designed to be exceptionally safe to use. The fast detecting circuitry reduces the likelihood of damage to the instrument if accidentally connected to live circuits or across phases.

- Meets the international requirements of IEC61010, IEC61557, FCC and IC.
- Live circuit detection and test inhibit on all measurements with user notification (except for direction of rotation measurements).
- User selectable insulation test terminal lockout voltage 25 V, 30 V, 50 V, 75 V (default is 50 V).
- Detection and inhibit functions when the protection fuse has failed.
- Suitable for use on CAT III 600 V systems.

### Insulation resistance tests

- Resistance range 100  $\Omega$  up to 200 G $\Omega$ .
- Supports PI, DAR, Timed and Temperature Compensation.
- Stabilised insulation test voltage accurate to -0% +2%  $\pm$ 2 V, which provides a more accurate test voltage without the risk of over-voltage damage to circuits or components. The output voltage is maintained between 0 and 2% throughout the test range.
- Where a nonstandard test voltage is required, a variable range allows the exact test voltage to be selected from 10 V up to 999 V and is subject to the same stabilised output control.
- Dedicated buzzer button either ON, VISUAL or OFF.

- Adjustable buzzer for minimum resistance limit (0.5 M $\Omega$  up to 1000 M $\Omega$ ).
- Buzzer sounds on test pass.

### Voltmeter

- Measures ac 10 mV up to 1000 V; dc 0 to 1000 V; TRMS (15 Hz up to 400 Hz).
- Three phase supply and direction of rotation.

### Continuity (resistance) tests

- Single automatic resistance range from 0.01  $\Omega$  to 1.0 M $\Omega$ .
- Automatic test current selection uses the preferred test current for the load resistance under test (200 mA up to 4  $\Omega$ ).
- Bi-directional tests option automatically reverses the current without reconnecting leads.
- Lead resistance compensation (NULL) operates up to 10  $\Omega$  of resistance.
- Dedicated buzzer switch either ON, VISUAL or OFF.
- Adjustable buzzer for maximum resistance limit (1  $\Omega$  to 200  $\Omega$  in 12 steps).
- Buzzer sounds on test pass.

### DLRO four wire Kelvin low resistance

- Automatic resistance range from 1 m $\Omega$  up to 10  $\Omega$ .
- Selectable auto or manual test.
- Bi-direction or single direction.
- Bi-directional tests option automatically reverses the current without reconnecting leads.
- 200 mA test current.

### Motor direction of rotation

Tests the direction of rotation of a motor under test and displays the phase sequence on screen.

### Inductance, capacitance and resistance meter (LCR)

Auto inductive, capacitive and resistive test. Frequency selectable to 120 Hz or 1000 Hz. In AUTO mode, the IMT100 automatically determines if the main element of the load is inductive, capacitive or resistive and displays the result on screen.

Selectable inductance and capacitance test.

### Temperature

The supplied thermocouple CAT III 600 V, allows temperature test and insulation resistance compensation.

### Display

Full colour graphic display makes the IMT100 simple to understand and easy to use.

## IMT100 and IMT100X Industrial Multi Tester

### Guard terminal

The Guard Terminal (G) provides a return path for leakage currents, preventing insulation measurement errors.

It improves accuracy when surface contamination affects equipment, connectors, or cables.

### Streamlined Test Management

Create, view, and delete asset IDs to keep test results organized. Export data to USB or CertSuite Asset via Bluetooth, stream live results for instant analysis, and generate detailed reports. Overwrite previous entries with updated test results for accuracy.

### Instrument software updates

Occasional information bulletins and software updates may be issued on the Megger web site.

## SPECIFICATIONS

All quoted accuracies are at 20 °C (68 °F).

### Insulation resistance

Volts	Accuracy
50 V	10 GΩ ±2% ±2 digits ±4.0% per GΩ
100 V	20 GΩ ±2% ±2 digits ±2.0% per GΩ
250 V	50 GΩ ±2% ±2 digits ±0.8% per GΩ
500 V	100 GΩ ±2% ±2 digits ±0.4% per GΩ
1000 V	200 GΩ ±2% ±2 digits ±0.2% per GΩ
<b>Polarisation index (PI):</b>	10 min / 1 minute ratio

### Dielectric absorption ratio (DAR):

User configurable 15 s or 30 s t1 start time with t2 fixed at 60 s

### Guard terminal performance

<5% error at 500 kΩ parallel circuit resistance with 100 MΩ load

**Resolution** 0.1 kΩ

**Short circuit/charge current** 2 mA +0% -50% (IEC61557-2)

### Terminal voltage accuracy

-0% +2% ±2 V

**Test current** 1 mA at min. pass value of insulation to a max. of 2 mA

**Operation range** 0.10 MΩ to 1.0 GΩ (IEC61557-2)

**Leakage current display** 0.1 uA resolution 10% (±3 digits)

**Voltage display** ±3% ±2 digits ±0.5% of rated voltage

**Note:** Above specifications only apply when high quality silicone leads are being used - as supplied with the instrument.

### Continuity

**Measurement** 0.01 Ω to 1 MΩ (0 to 1000 kΩ analogue scale)

**Accuracy** ±3% ±2 digits (0 to 99.9 Ω)  
±5% ±2 digits (100 Ω - 500 kΩ)

**Test current** 200 mA (-0 mA +20 mA)  
(0.01 Ω - 4 Ω)

**Polarity** Single or Dual (factory default) polarity

**Lead resistance** Null up to 10 Ω

**Selectable current limit** 20 mA and 200 mA

### Capacitance

**Range** 0.1 nF - 1 mF

**Accuracy** ±5.0% ±2 digits (1 nF - 10 μF)

### Voltmeter

**Range** DC: 0 - 1000 V  
AC: 10 mV - 1000 V  
TRMS sinusoidal (15 Hz - 400 Hz)

**Accuracy** DC: ±2% ±2 digits (0 - 1000 V)  
AC: ±2% ±2 digits  
(10 mV - 1000 V TRMS)

**Frequency range** 15 - 400 Hz (50 mV - 1000 V)

**Frequency resolution** 0.1 Hz

**Frequency accuracy** ±0.5% ±1 digit

**Diode Test** Diode test accuracy: ±2% ±2 digits  
0.01 V to 3.00 V

**Display range:** 0.00 V to 3.00 V

### Temperature measurement and compensation

**Thermocouple** Type T (Type K and Type J)

**Thermocouple range** -20 °C to 200 °C (4 °F - 392 °F)

**Instrument range** -20 °C to 1000 °C (4 °F - 1832 °F)

**Instrument resolution** 0.1 °C (0.18 °F)

**Instrument accuracy** ±1.0 °C ±20 digits (1.8 °F). (Basic accuracy stated assumes forward and reverse measurements.)

### DLRO four wire Kelvin low resistance

**Test current** 200 mA DC

**Range** 1 mΩ to 10 Ω

**Resolution** 0.01 mΩ

**Accuracy** ±0.25% rdg. ±10 digits, accuracy stated includes forward and reverse measurements.

### Inductance

#### Instrument accuracy

Range	Accuracy	Test Frequency
1 H	±(0.7 % +(Lx/10000) %) +5 digits	1 kHz
200 mH	±(1.0 % +(Lx/10000) %) +5 digits	120 Hz
	±(0.7 % +(Lx/10000) %) +5 digits	1 kHz
20 mH	±(2.0 % +(Lx/10000) %) +5 digits	120 Hz
	±(1.2 % +(Lx/10000) %) +5 digits	1 kHz
2 mH	±(2.0 % +(Lx/10000) %) +5 digits	1 kHz only

### Results storage

**Storage capacity** 256 test results (date / time stamped)

**Data download** USB Type A (USB Mass Storage Device)

# IMT100 and IMT100X Industrial Multi Tester

<b>Power</b>	
<b>Battery</b>	6 x IEC HR6 1.2 V NiMH fitted optional: 6 x IEC LR6 1.5 V Alkaline (AA) IEC FR6 1.5 V Lithium (LiFeS <sub>2</sub> ).
<b>Battery life</b>	10 motors per (complete suite of tests at 100 V into 100 MΩ) IEC61557-2 - test cycle, 1200 insulation tests with duty cycle of 5 s testing on 25 s standby @ 500 V into 0.5 MΩ.  IEC61557-4 test cycle, 1200 continuity tests with duty cycle of 5 s testing on 25 s standby on 1 Ω resistance.
<b>Battery charging</b>	Mains battery charger kit.
<b>Safety protection</b>	IEC61010-1 CAT III 600 V
<b>EMC</b>	Industrial IEC61326 FCC ID: WAP3026 IC: 7922A-3026
<b>Temperature coefficient</b>	<0.1% per °C up to 1 GΩ
<b>Environment</b>	
<b>Operating temperature range</b>	-10 °C to 50 °C (14 °F to 122 °F)
<b>Storage temperature range</b>	-25 °C to 50 °C (-13 °F to 122 °F)
<b>Humidity</b>	90% RH at 40 °C (104 °F) max.
<b>Calibration temperature</b>	20 °C (68 °F)
<b>Maximum altitude</b>	3000 m (9843 ft.)
<b>IP rating</b>	IP54
<b>Physical</b>	
<b>Display</b>	Full LCD colour screen with user configurable backlight
<b>Languages</b>	English, French, German and Spanish.
<b>Dimensions</b>	228 x 105 x 75 mm (8.98 x 4.1 x 2.95 in)
<b>Weight</b>	0.93 kg (2.02 lbs)
<b>Fuse</b>	x2 500 mA (FF) 1000 V 32 x 6 mm ceramic fuse, high break capacity HBC, 30 kA minimum. Glass fuses must not be installed.

## ORDERING INFORMATION

Description	Part number
IMT100 Industrial Multi Tester	1015-518
IMT100X Industrial Multi Tester (Bluetooth®)	1017-031
<b>Included accessories:</b>	
Hook strap assembly	
Multipurpose industrial carry case	
SP5 remote probe	1007-157
Crocodile clips, (red, black and blue) CAT IV 600 V	
Temperature probe, T type CAT III 600 V	1012-067
<b>IR lead set (comprising of):</b>	1012-069
3 x Grabber Clips (Red, Black and Blue) CAT III 1000 V, CAT IV 600 V 3 x 4 mm Test leads, 2 m length, 1 end Right Angle, 1 end straight (red, black and blue), CAT III 1000 V, CAT IV 600 V 3 x Test probes (red, black and blue), long reach (100 mm), CAT IV 600 V	
<b>Kelvin clip lead set CAT III 600 V (comprising of):</b>	1011-928
2 x Kelvin Clip leads, 2 meters, 4 mm Right Angled Connectors (4), Single (2-core) cable.	
<b>Kelvin probe lead set CAT III 600 V (comprising of):</b>	1011-929
2 x Kelvin Probe leads, 2 meters, 4 mm Right Angled Connectors (4), Single (2-core) cable.	
Replaceable Kelvin Probe Pins (Pack of 4)	1012-064
<b>PV Test Lead Set adaptors (comprising of):</b>	1002-549
(2), MC4-type one red and one black connector adaptors (2), MC3-type black connector adaptors	
Test probe set, long reach, CAT II 1000 V	1012-065
Certificate of test (EN/FR/ES/DE)	
Certificate of calibration	
Mains charger kit	1007-464
6 x AA rechargeable batteries NiMH (fitted)	
Quick start guide	
<b>Optional accessories:</b>	
Grabber clip lead set CAT III 1000 V, CAT IV 600 V	1012-069
Test probe set, long reach CAT IV 600 V	1012-066

**Megger**®