

Product data sheet



HG 2320 ESD
Electrostatic Discharge Heat Gun

Technical Specifications

Voltage:	120 VAC / 60 Hz
Power:	1600 watts
Amps:	13.3
Surface Conductivity:	10 ⁴ ohms
Airflow Rate:	3.6 - 17.6 cfm. (continuously variable)
Stages:	2 (continuously variable)
Power Cord:	Industrial grade rubber, length: 6 ft
Motor:	Brush motor
Heating Element:	Ceramic heating element
Motor Lifetime:	1000 hours
Accessories:	Use of standard accessories
Temperature:	120-1200 ° F
Net Weight:	2.19 lbs
Dimensions:	9.96" x 3.41" x 7.87"
(L x W x D)	

Single Sell Pack:	Dimensions: 10.20" x 3.54" x 9.33"
	Weight: 2.60 lbs

Features:	Higher durability (+20%), optimized weight balance, LCD-Display, 4 settings programmable, heat build-up warning, hanging ring, easily replaceable power cord, residual heat indicator, optional temperature scanner and fine dist filter
-----------	--

Warranty:	1 year
-----------	--------



RoHS
Compliant

ISO
9001:
2015
14001:
2015

UPC Code	Product No.
0 18139 73503 8	110073503

