

# 1750

## Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- · Strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- 3-piece foam set
- · Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- · Easy open Double Throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



## CONFIGURATIONS



1750 Standard



1750NF No Foam



1750WF With Foam

#### **DIMENSIONS**

Interior (L×W×D) 50.50 x 13.50" x 5.25 (128.3 x 34.3 x 13.3 cm) Exterior (L×W×D) 53.00 x 16.00" x 6.12 (134.6 x 40.6 x 15.5 cm)

**Lid Depth** 1.75" (4.4 cm) **Bottom Depth** 3.50" (8.9 cm) **Total Depth** 5.25" (13.3 cm) Int Volume 2.07 ft3 (0.059 m3) Padlock Hole Diameter 5/16" (12.7 cm)

## **MATERIALS**

Body Polypropylene

Latch ABS **O-Ring** Polymer Stainless Steel **Pins Foam** 1.3 lb Polyurethane



**Purge Body** ABS

**Purge Vent** 3 Micron Hydrophobic Non-Woven

## **COLORS**

Black Desert Tan OD Green

## WEIGHT

**Weight With Foam** 25.57 lbs (11.6 kg) Weight Empty 23.59 lbs (10.7 kg) 187.39 lbs (85 kg) **Buoyancy Master Pack Weight** 25.65 lbs (11.6 kg)

## **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) Maximum Temperature 210°F (98.9 °C)

## **CERTIFICATIONS**

IP67

Def Stan 81-41 **STANAG 4280** 

## FOAM PROPERTIES

Layer 1 (Lid) 1.63" Pad Layer 2 (Base) 1.63" Pad Layer 3 (Base) 1.63" Pad

## OTHER

2 Wheels **Master Pack** 1 Nameplate yes Military yes

## **ACCESSORIES**







1753 Replacement O-ring



1506TSA TSA Lock



1500D Desiccant Silica Gel



PL2 Padlock (2 pack)