

Fluke 179 IMSK Industrial Multimeter Service Kit



TWO VERSATILE, RELIABLE TOOLS TO HELP SOLVE YOUR FRONT-LINE TROUBLESHOOTING PROBLEMS

- A full-featured, true-rms multimeter combined with a rugged, reliable basic true-rms clamp meter
- Ideal for troubleshooting electrical and electronic systems
- Measures up to 1000 V ac or dc (179 DMM) and up to 400 A ac (323 clamp)

The right tools, right where you need them

Fluke 179 IMSK Industrial Multimeter Service Kit

This kit combines the Fluke 179 True-RMS DMM and the Fluke 323 True-RMS clamp meter. Both tools are rugged, reliable and accurate, as well as extremely easy to operate.

Fluke 179 True-RMS Digital Multimeter


The Fluke 179 is the preferred solution for professional technicians around the world. It includes the features you need to troubleshoot and repair electrical and electronic systems:

- Delivers accurate true-rms AC current and voltage plus frequency, capacitance, resistance, continuity and diode measurements
- Increases productivity with manual and automatic ranging, Display Hold, Auto Hold, and Min/Max-average recording

Fluke 323 True-RMS Clamp Meter

The Fluke 323 clamp meter provides true-rms measurements, optimized ergonomics, and large display for efficient troubleshooting. It's designed to perform in the toughest environments and provide noise-free, reliable results, so you can confidently diagnose problems almost anywhere.

- Rugged, reliable basic true-rms clamp meter for measuring current up to 400 A
- Measures AC current to 400 A
- Measures AC voltage and DC voltage to 600 V
- Provides true-rms AC voltage and current for accurate measurements on non-linear signals
- Measures resistance to 4 kΩ with continuity detection
- Features a CAT III 600 V, CAT IV 300 V safety rating



Specifications

Fluke 179 True-RMS Digital Multimeter

Detailed specifications

Voltage DC	Accuracy ¹	± (0.09 % + 2)
	Max. resolution	0.1 mV
	Maximum	1000 V
Voltage AC	Accuracy ¹	± (1.0 % + 3)
	Max. resolution	0.1 mV
	Maximum	1000 V
Current DC	Accuracy ¹	± (1.0 % + 3)
	Max. resolution	0.01 mA
	Maximum	10 A
Current AC	Accuracy ¹	± (1.5 % + 3)
	Max. resolution	0.01 mA
	Maximum	10 A
Resistance	Accuracy ¹	± (0.9 % + 1)
	Max. resolution	0.1 Ω
	Maximum	50 MΩ
Capacitance	Accuracy ¹	± (1.2 % + 2)
	Max. resolution	1 nF
	Maximum	10,000 µF
Frequency	Accuracy ¹	± (0.1 % + 1)
	Max. resolution	0.01 Hz
	Maximum	100 kHz
Temperature	Accuracy ¹	± (1.0 % + 10)
	Max. resolution	0.1 °C
	Maximum	-40 °C / 400 °C

Environmental specifications

Operating temperature	-10° C to +50° C
Storage temperature	-30° C to +60° C
Humidity (without condensation)	0 % – 90 % (0° C – 35° C) 0 % – 70 % (35° C – 50° C)

Safety specifications

Overvoltage category	EN 61010-1 to 1000 V CAT III EN 61010-1 to 600 V CAT IV
Agency approvals	UL, CSA, TÜV listed and VDE Pending

Mechanical and general specifications

Size	43 x 90 x 185 mm
Weight	420 g
Warranty	Lifetime
Battery life	Alkaline ~200 hours typical, without backlight

1. Accuracies are best accuracies for each function

Fluke 323 True-RMS Clamp Meter**Detailed specifications**

AC current	Range	400.0 A
	Accuracy	2 % \pm 5 digits (45 Hz to 65 Hz) 2.5 % \pm 5 digits (65 Hz to 400 Hz)
DC current	Range	-
	Accuracy	-
AC voltage	Range	600.0 V
	Accuracy	1.5 % \pm 5 digits
DC voltage	Range	600.0 V
	Accuracy	1.0 % \pm 5 digits
Resistance	Range	400.0 Ω / 4000 Ω
	Accuracy	1.0 % \pm 5 digits
Continuity	\leq 70 Ω	
Capacitance	-	
Frequency	-	
AC response	True-rms	
Backlight	-	
Data hold	Yes	
Contact temperature	-	
Min/Max	-	
Size	H x W x D (mm)	207 x 75 x 34
	Max wire diameter	30 mm (600 MCM)
	Weight	265 g
Category rating	CAT III 600 V CAT IV 300 V	
Warranty	Two-year	

Ordering information

Fluke 179 IMSK Industrial Multimeter Service Kit

Included

Fluke 179 True-RMS Digital Multimeter
 Fluke 323 True-RMS Clamp Meter
 80BK-A DMM Temperature Probe
 TL75 Hard Point Test Lead Set
 AC175 Threaded Alligator Clip Set

Fluke. Keeping your world
up and running.®

©2019 Fluke Corporation.
 Specifications subject to change without notice.
 Printed in U.S.A. 10/2019 6012857a-en
 Modification of this document is not permitted
 without written permission from Fluke Corporation.