



Model
DKT-1

Pocket-Size Thermocouple Thermometer

Selectable °F/°C, Accepts Mini-Plug Input



The Model DKT-1 Pocket-Size Thermocouple Thermometer accurately monitors temperatures in a variety of applications. The wide measurement range and selectable engineering units allow users to easily view readings in either °F or °C. The automatic power down feature conserves battery life. This compact thermometer accepts any K-type thermocouple sensors (sold separately) with mini-plug connectors.

Model DKT-1, Thermocouple Thermometer

ACCESSORIES

- 1818-0074, Immersion Probe
- 1818-0078, Penetration Probe
- 1818-0082, Surface Probe
- 1818-0085, Air Duct Probe

SPECIFICATIONS

Measurement Range: -83.2 to 1999°F (-64 to 1400°C).

Operating Temperature: 32 to 122°F (0 to 50°C).

Accuracy: ± 1% of reading or 1.8°F (1.0°C).

Probe Connection: K type mini-jack.

Resolution: 0.1°F/°C.

Power Requirements: 3 V CR2032 lithium metal battery, installed functional, user replaceable.

Battery Life: Estimated 100 hours continuous use.

Weight: 1.42 oz (40.15 g).

Agency Approvals: CE.

OPTION

For NIST traceable calibration certificate, use order code NISTCAL-TG.