

2-VALVE ALUMINUM MANIFOLD

The rough-and-tumble durability of our 4-Valve with the simplicity of a 2-Valve design.



Extra Confidence

Built to last with a forged aluminum body. Designed to be leak-resistant with replaceable stainless steel valve seats, SAE-style O-rings and a securely seated, large sight glass.



Comfortable Grip

A rubberized handle makes it easier to use in wet and dirty environments.



Easy to Read

Improved graphics and high-contrast colors deliver precise readings at a glance.



Glows in the Dark

Light-activated paint illuminates, so you won't be left in the dark.



Built-in Pressure Reminder

A pressure reminder allows you to set the pressure ring and reference it later.



2-Valve
Aluminum
Manifold
1839134



Rubberized handles are optimally sized for easy turns.



A permanent location for the temperature clamps offers quick and convenient storage.



With a forged aluminum body, it can stand up to the roughest, toughest conditions.

Product Specifications

Item Numbers/Product Descriptions					
Refrigerants	Item Numbers	Product Descriptions	Temp.	Pressure Range Low	Pressure Range High
R22-134A-404A	1839126	2V22134404	F	-30" HG/120/350 psi	0/500 psi
R22-404A-410A	1839134	2V22404410	F	-30" HG/300/500 psi	0/800 psi
R10A	1839113	2V410	F/C	-30" HG/300/500 psi	0/800 psi
Accuracy		Class 1 - 1% Accuracy (full scale)			
Gauge Connection Type		1/8" NPT Male Fitting			
Valve Type		Double O-ring Piston Style			
Valve Seat (Orifice)		Replaceable Stainless Steel (SAE-style straight thread with O-ring)			
Sight Glass		Bonded Steel with SAE-style straight thread with O-ring			
Charge Ports		1/4" (quantity 3)			
Dimensions					
Length		8-7/8"			
Width		1-3/4"			
Height		7-1/8" without hook			
Weight		2.5 lbs.			