

4-VALVE ALUMINUM MANIFOLD WITH HOSES & DUAL READOUT THERMOMETER

Product Specifications

Item Numbers/Product Descriptions					
Refrigerants	With 60" Hoses and Ball Valve Adapters		Temp.	Pressure Range Low	Pressure Range High
R410A	1839110	4V410HD	F/C	-30" HG/300/500 psi	0/800 psi
R22-404A-410A	1839131	4V22404410HD	F	-30" HG/300/500 psi	0/800 psi

Accuracy	Class 1 - 1% Accuracy (full scale)
Gauge Connection Type	1/8" NPT Male Fitting
Valve Type	Double O-ring Piston Style
Valve Seat (Orifice)	Replaceable Stainless Steel (SAE-style straight thread with O-ring)
Sight Glass	Bonded steel with SAE-style straight thread with O-ring
Vacuum Port	3/8" full bore (quantity 1)
Charge Ports	1/4" (quantity 3)
Hoses Included	1839143 H60BVS4 60" Hoses with Ball Valve Adapters - Set of 4
Thermometer Included	1839106 DROT2TCC Dual Readout Thermometer
Two Thermocouples Included	1839108 TCC Thermocouple Clamp

Dimensions	
Length	8-7/8"
Width	4"
Height	7-1/8" without hook
Weight	7.3 lbs.



4-Valve Aluminum
Manifold with Hoses &
Dual Readout Thermometer
1839131