



#### Floor Mat Kit Item Number

| Size                      | Black                    |
|---------------------------|--------------------------|
| 48" x 72" (1.2 m x 1.8 m) | <a href="#">1964 4X6</a> |

#### Floor Mat Kit Includes:

- 1 Floor Mat, size as specified
- 1 [3040](#) 15' (4.6 m) Ground Cord
- 2 Female 3/8" Snaps (Snaps installed on long side of mat)

#### Floor Roll Item Number without Hardware

| Size                       | Black                     |
|----------------------------|---------------------------|
| 36" x 60' (0.9 m x 18.3 m) | <a href="#">1964 3X60</a> |

# SCS

© 2019 DESCO INDUSTRIES INC  
Employee Owned



Made in the  
United States of America



1964 Series Conductive Vinyl Flooring is designed to rapidly drain off static electricity meeting ANSI/ESD S20.20 tested per ANSI/ESD S4.1 & ESD TR53. Providing a static-safe conductive work area for a wide variety of applications where ESD properties are required, 1964 Series Vinyl Flooring is non-carbon loaded, non-sloughing and permanently conductive.

| Properties                            | Typical Value                             |
|---------------------------------------|-------------------------------------------|
| Material                              | Homogeneous Polymer Matrix of durable PVC |
| Color*                                | Black                                     |
| Emboss Pattern                        | Pebble                                    |
| Thickness                             | 0.125" $\pm$ 0.013" (3.2 mm $\pm$ 0.3 mm) |
| Tensile                               | 600 lb/in <sup>2</sup>                    |
| Elongation                            | 150 %                                     |
| Tear                                  | 100 lb/in                                 |
| Hardness (top)                        | 75 $\pm$ 5 Shore A                        |
| Resistance<br>Surface to Ground (Rtg) | < 1 x 10 <sup>6</sup>                     |
| Service Temperature                   | -20 °F to +200 °F (-6.7 °C to +93 °C)     |

; and mills

**RoHS, REACH and Conflict Minerals, Statement**

See the Desco Industries RoHS, REACH, and Conflict Minerals Statement:

\_\_\_\_\_  
\_\_\_\_\_

**1964 SERIES CONDUCTIVE VINYL FLOORING**

|  |                                   |                                 |
|--|-----------------------------------|---------------------------------|
|  | <b>DRAWING<br/>NUMBER</b><br>1964 | <b>DATE</b><br>November<br>2019 |
|--|-----------------------------------|---------------------------------|