

1732 (64) SPACE CREATED BY 3 SPACER PADS WHEN SURFACE MOUNTED. DO NOT OBSTRUCT. PROVIDES PATH FOR RELIEF OF OVERPRESSURE.

RUBBER PRESSURE RELIEF PLUG WILL UNSEAT ITSELF WHEN PRESSURE IS OVERPRESSURIZED.

(3) 6-32 X 3/16 (4.78) DEEP HOLES EQUALLY SPACED ON A 04-1/8 (104.78) BOLT CIRCLE FOR PANEL MOUNTING.

Model 1732 Dimensions:
 Front View: 04-3/4 (120.65) diameter.
 Side View: 1-1/4 (31.75) height, 15/32 (11.91) mounting flange, 1-11/16 (42.86) total height, 17/32 (13.49) top flange.
 Rear View: 1/8 FEMALE NPT HIGH PRESSURE CONNECTION, 1/8 FEMALE NPT LOW PRESSURE CONNECTION, 11/16 (17.46) diameter, 1/2 (12.70) height, 1/8 FEMALE NPT HIGH PRESSURE CONNECTION, 1/8 FEMALE NPT LOW PRESSURE CONNECTION.

Model 1733 Dimensions:
 Front View: 05-1/2 (139.70) diameter, MOUNTING RING.
 Side View: 1-1/4 (31.75) height, 15/32 (11.91) mounting flange, 04-1/2 (114.3) diameter, 17/32 (13.49) top flange, 05 (127) total height, 04-47/64 (120.27) diameter, 2-17/32 (64.70) height, 3/16 (4.78) bottom flange.
 Rear View: 1/8 FEMALE NPT HIGH PRESSURE CONNECTION, 1/8 FEMALE NPT LOW PRESSURE CONNECTION, 11/16 (17.46) diameter, 1/2 (12.70) height, 1/8 FEMALE NPT HIGH PRESSURE CONNECTION, 1/8 FEMALE NPT LOW PRESSURE CONNECTION.

04-3/4 (120.65) PANEL CUTOUT

sales@calcert.com