


Tinsley Thickness Gauge



- **Economical**
- **Convenient**
- **Reaches every contour easily**
- **Gravity compensated**

DESCRIPTION

The Tinsley Thickness Gauge is designed for measuring the dry-film thickness of any nonmagnetic material such as paint, plastic, etc., or plating such as zinc or chromium over a ferrous base (iron or steel).

The thickness gauge consists of a special lightweight magnet attached to a spring and contained within a pencil-like tube.

To take a measurement, the exploring head or magnet is placed on the surface and the body of the gauge is drawn away, thus extending the spring. The spring extension, the amount of which is observed on the scale, is proportional to the force required to detach the magnet from the surface. The reading is taken when the magnet breaks away from the surface, and the thickness is read directly from the scale.

The standard scale for nonmagnetic coatings on mild steel also applies to coatings on cast iron and low-alloy steels, without appreciable error, and to coatings on high-alloy steels, with a small correction for thicknesses of less than 0.001 in. (0.025 mm).

When used on bases other than mild steel, the gauge will still give repeatable results. For accurate work, a separate calibration is advised for each particular application. This can normally be carried out by the customer and a correction chart made.

APPLICATIONS

The Tinsley Thickness Gauge is ideal for paint and plating shops, and for manufacturing processes in the automotive, costume jewelry, alloy casting and other industries. It reduces loss of materials such as paint and precious metal coatings and helps ensure adherence to correct tolerances in precision parts.

FEATURES AND BENEFITS

- Easy to use and carry — pencil size with pocket clip. Tests can be made quickly and simply, requiring no setup time.
- Usable on curved or irregular surfaces
- Not affected by vibrations or temperature — special stabilized magnet used
- Nondestructive test


SPECIFICATIONS

Range

0.0002 to 0.015 in. (0.2 to 15 mils)
5 to 500 microns

Accuracy

±15% or 0.0001 in. (0.0025 mm),
whichever is greater



ORDERING INFORMATION	
Item (Qty)	Cat. No.
Tinsley Thickness Gauge	280282

UK
Archcliffe Road, Dover
CT17 9EN England
T (0) 1 304 502101
F (0) 1 304 207342

UNITED STATES
4271 Bronze Way
Dallas, TX 75237-1018 USA
T 1 800 723 2861
T 1 214 333 3201
F 1 214 331 7399

OTHER TECHNICAL SALES OFFICES
Norristown USA, Toronto CANADA,
Mumbai INDIA,
Le Raincy FRANCE, Cherrybrook
AUSTRALIA, Guadalajara SPAIN
and The Kingdom of BAHRAIN.

ISO STATEMENT
Registered to ISO 9001:1994 Reg no. Q 09250
Registered to ISO 14001 Reg no. EMS 61597
TINSLEYGAUGE_DS_En_V01
www.megger.com
Megger is a registered trademark