



2 Block Dry Block Heaters



Versatile Block Heaters Designed for Everyday Use with Accessories for Every Application

Versatile Dry Block Heaters are ideal for applications that require temperature stability. Close tube-to-block contact enables maximum heat retention, resulting in efficient heating. Digital models offer exceptional temperature uniformity and stability for repeatable results, while non-digital models are an economical choice. All units hold optional interchangeable modular blocks with over 40 choices. Blocks are easy to use, no tools required.

Standard Features:

- **Delivering Exceptional Temperature Stability and Uniformity**
Three models to customize your application. All models offer exceptional temperature uniformity with outstanding temperature stability.
- **Heated Lid Model Reduces Condensation on Lids to Maintain Sample Integrity**
A second heater in the lid helps minimize condensation to maintain sample integrity, providing reliable, repeatable results. Easily monitor settings with independent displays for temperature and time.
- **Calibrate to an External Temperature Device with Temperature Calibration Mode**
Digital models with user calibration feature allows you to match the Block Heater's display to your known external temperature standard which improves the temperature accuracy of the system.

2 Block Dry Block Heaters

Model	HB2AL	HB2DG	HB2DGH
Control	Non-Digital	Digital	Digital
Temperature Range	Low Ambient + 5 °C – 100 °C, High 75 °C – 150 °C	Ambient + 5 °C – 120 °C	Ambient + 5 °C – 100 °C
Stability @ 37 °C	± 1.5 °C	± 0.1 °C	
Uniformity @ 37 °C	± 0.1°C		
Heat Up Time to 100 °C	≤ 16 min		≤ 30 min
Temperature Calibration	NA	•	
Number of Blocks	2		
Overshoot Protection	NA	10 °C above set point	
Working Environment	64 ° F – 91 °F, 20% – 80% relative humidity, non-condensing / 18 °C – 33 °C, 20% – 80% relative humidity, non-condensing		
Power	120V, 1.75A, 50/60Hz		120V, 3A, 50/60Hz
Power Consumption	210 W		400 W
Dimensions (W × L × H)	8 × 15.4 × 3.5 in. / 203 × 391 × 89 mm		8 × 15.4 × 7 in. / 203 × 391 × 178 mm
Net Weight	6.2 lb / 2.8 kg		6.8 lb / 3.1 kg

Other Standard Features and Equipment

Touchpad control and audible alarm (digital models), painted steel housing, digital models include support rod holder with locking knob, detachable 3-wire cord and plug (included)

Compliance

- **Product Safety:** CAN/CSA C22.2 61010-1, CAN/CSA C22.2 61010-2-010, CAN/CSA C22.2 61010-2-051, UL 61010-1
- **Electromagnetic Compatibility:** ICES-003 Class A, FCC Part 15 Class A
- **Compliance Marks:** TÜV SÜD


Accessories

Module Block 10 mm Test Tube, 24 Wells 30400151
 Module Block 12/13 mm, 20 Wells 30400152
 Module Block 15/16 mm, 12 Wells 30400153
 Module Block 20 mm Test Tube, 8 Wells 30400154
 Module Block 25 mm Test Tube, 6 Wells 30400155
 Module Block Combo - Test Tube Combination Block:
 6 mm, 12/13 mm, 25 mm 30400156
 Module Block 0.5 mL Microtaper, 30 Wells 30400157
 Module Block 6 mm Test Tube, 30 Wells 30400158
 Module Block 1.5 mL Microtaper, 20 Wells 30400159
 Module Block Solid 30400160
 Module Block Cuvette - 12 Cuvet, 2 Wells 30400161
 Module Block 11.5/1.5 mL Microcentrifuge, 20 Wells
 30400162
 Module Block 250 Microliter/6 mm, 30 Wells 30400163
 Module Block Titer Plate 30400164
 Module Block 12/13 mm, 16 Wells 30400165
 Module Block Solid Double 30400166
 Module Block 35 mm Test Tube, 4 Wells 30400167
 Module Block 50 mL Conical Centrifuge, 5 Wells ... 30400168
 Module Block 0.2 mL Micro, 80 Wells 30400169
 Module Block 0.2 mL Micro, 64 Wells 30400170
 Module Block 0.2 mL 96 Hole Double Block 30400171

Module Block 15 mL Conical Centrifuge, 12 Wells ... 30400172
 Sand Bath, 2 Block Unit 30400174
 Sand, 0.5 kg (1 lb) Bag 30400177
 Stainless Steel Shot, 0.5 kg (lb) 30400178
 Cover Low-Temperature 2 Block* 30400179
 Module Block For Vials 12 mm, 20 Wells 30400182
 Module Block For Vials 15 mm, 20 Wells 30400183
 Module Block For Vials 17 mm, 12 Wells 30400184
 Module Block For Vials 19 mm, 12 Wells 30400185
 Module Block For Vials 21 mm, 9 Wells 30400186
 Module Block For Vials 23 mm, 8 Wells 30400187
 Module Block For Vials 25 mm, 8 Wells 30400188
 Module Block For Vials 28 mm, 6 Wells 30400189
 Module Block For Vials 16 mm, 15 Wells 30400190
 Module Block, 2.0 mL Tube, 20 Wells 30400191
 Module Block, 2.0 mL Corning Tube, 20 Wells 30400192
 Module Block Combo - Centrifuge Tube Configuration:
 50 mL-2 Wells, 15 mL-3 Wells, 1.5 mL-4 Wells 30400193
 Module Block Combo - Micro Tube Combination:
 2 mL-5 Wells, 1.5 mL-10 Wells, 0.5 mL-6 Wells 30400194
 Module Block 17/18 mm, 12 Wells 30400195
 Stainless Steel Probe Kit** 30400246

*NA for HB2DGH **NA for HB2AL

Dimensions



75613_B 20200227 © Copyright OHAUS Corporation

The management system governing the manufacture of this product is ISO 9001:2015 certified.



1.888.610.7664

 www.calcert.com

sales@calcert.com