

Description	Part No.
QUICK DISCONNECT CONNECTORS	
M12 Eurofast male quick disconnect connection installed into the sensors conduit and pre-wired to the control board	530-0871
7/8" Minifast male quick disconnect connection installed into the sensors conduit and pre-wired to the control board	530-0872
Field-wireable M12 Eurofast straight female connector, plastic (PBT Or Nylon)	318-0236
Field-wireable 7/8" minifast straight female connector, glass-filled nylon body	318-0237
4/18 AWG YELLOW PVC; bulk cable, coil, with yellow polyvinyl chloride outer jacket, wire complement: altogether 4X18 AWG wires. Non-returnable. Sold by the foot.	398-0585
DNET QUICK DISCONNECT CONNECTORS	
7/8" Tee Quick Connector - DNet	318-0257
7/8" Female Field Wireable Quick Connector - DNet	318-0258
7/8" Male Field Wireable Quick Connector - DNet	318-0259
7/8" Female End Cap - DNet	318-0260
DNet Cable 5M with 7/8" Male/Female Connectors	398-0595
DNet Cable 10M with 7/8" Male/Female Connectors	398-0596
DNet Cable 15M with 7/8" Male/Female Connectors	398-0597
DNet Cable 1M with 7/8" Male/Female Connectors	398-0598
DNet Cable (sold by the Meter)	398-0599