Short portrait: Series 96

- Extra stiff aluminium rectangular profile with reinforcing ribs.
- Measuring accuracy in normal position 0.5 mm/m and in reverse position 0.75 mm/m.
- Two milled measuring surfaces of up to 122 cm.
- Patented anti-slip stoppers make for a firm seat when marking.
- Removeable end caps alleviate use right in the corner.
- Shock-absorbing end caps protect the spirit level profile if it falls.
- 10 years warranty.

STABILA -



Series 96

| Туре | | | | |
|-----------------------------------|------------------------------|---------|---|--|
| Accu | racy in normal p | osition | 1 | |
| Accu | acy in reverse p | oositio | า | |
| Meas | uring surfaces | | | |
| Vial t | ype | | | |
| End o | aps | | | |
| | | | | |
| Spec | ial feature | | | |
| | ial feature th / Art. No. | | | |
| | th / Art. No. | | | |
| Leng | th / Art. No. | | | |
| Leng 40 cr | th / Art. No. | | | |
| Leng 40 cr 61 cn | th / Art. No. | | | |
| Leng 40 cr 61 cn 81 cn | th / Art. No. | | | |
| Leng 40 cr 61 cn 81 cn | th / Art. No. | | | |
| 40 cm 61 cm 81 cm 100 cm | th / Art. No. | | | |

| 0 | 96-2 |
|----------|---------------------------------------------|
| ДΙ | 0.029° = 0.5 |
| = | 0.043° = 0.7 |
| T I | 2 X |
| * | 1 x horizonta 2 x vertical |
| Ш | Removeable Anti-slip stop Shock absor |
| | - |
| e e | |
| | 15225/3 |
| | 15226/0 |
| | 15227/7 |
| 101 | 15228/4 |
| 71 | 15229/1 |
| 9 | 15230/7 |
| 8 | 15231/4 |
| | 15232/1 |
| اھ | |

| 96-2 | 96-2 M |
|--------------------------------------------------------|--------------------------------------------------------|
| 0.029° = 0.5 mm/m | 0.029° = 0.5 mm/m |
| 0.043° = 0.75 mm/m | 0.043° = 0.75 mm/m |
| 2 X | 2 X |
| 1 x horizontal 2 x vertical | 1 x horizontal 2 x vertical |
| Removeable / Anti-slip stopper / Shock absorbers | Removeable / Anti-slip stopper / Shock absorbers |
| - | Rare-earth magnet |
| /- | 0/- |
| 15225/3 | 15852/1 |
| 15226/0 | 15853/8 |
| 15227/7 | 15854/5 |
| 15228/4 | 15855/2 |
| 15229/1 | 15856/9 |
| 15230/7 | 15857/6 |
| 15231/4 | 15858/3 |
| 15232/1 | |

| | 13 |
|---|----|
| m | |
| | |

96-2 K 0.029° = 0.5 mm/n

 $0.043^{\circ} = 0.75 \text{ mm}/$

Removeable / Anti-slip stopper /

Shock absorbers

Knocking protection

1 x horizontal

2 x vertical

16403/4

Patented anti-slip stoppers make for a firm seat when marking.



Type 96-2 M: Rare-earth magnets with additionally strong adhesive force. You always have your hands free in aligning and adjusting metal objects.



Type 96-2 K: Patented impact protection. Correct bricks, if out-of-line, with light taps of a trowel.

^{*} Continuous bridge over the horizontal vial increases the stability of the profile.