

3900A & 3900B ELECTRONIC INDICATORS



METROLOGY SOLUTIONS

NEW !



AGD GROUP 2 RANGES UP TO 1" AND 25.4MM

3900 Series Electronic Indicators have simple, powerful, easy-to-use functions, all at an attractive price. 3900A is Starrett's entry level electronic indicator. 3900B adds SPC output capability. All models are inch/metric. Available in English or metric stem diameter and screw thread.

FEATURES

- Large, easy-to-read LCD
- Reverse travel ($\pm$ control indicates direction)
- Zero setting at any position
- Long battery life
- 3/8" diameter stem on English models (8mm on metric models)
- #4-48 screw thread on inch/mm models (M2.5 X 0.45 thread on metric-only model)
- Lug-on-center back with additional flat back
- Dust cap
- Plastic storage case with form-fit foam insert

Cat. No.	EDP	Range		Resolution		Accuracy		Stem Diameter	Screw Thread
		in	mm	in	mm	in $\pm$	mm $\pm$		
3900A-5	62418	.5	12.7	.0005	0.01	.001	0.03	3/8"	#4-48
3900MA-5	62420	.5	12.7	.0005	0.01	.001	0.03	8mm	M2.5 x 0.45
3900A-1	62419	1	25.4	.0005	0.01	.001	0.03	3/8"	#4-48
3900MA-25	62426	1	25.4	.0005	0.01	.001	0.03	8mm	M2.5 x 0.45
3900B-5	62421	.5	12.7	.0005	0.01	.001	0.03	3/8"	#4-48
3900MB-5	62423	.5	12.7	.0005	0.01	.001	0.03	8mm	M2.5 x 0.45
3900B-1	62422	1	25.4	.0005	0.01	.001	0.03	3/8"	#4-48
3900MB-25	62427	1	25.4	.0005	0.01	.001	0.03	8mm	M2.5 x 0.45

Accessory

Part No.	EDP	Description
PT99492	65650	CR2032 Lithium 3 Volt Battery (Pack of 2)
1403-25N	62443	End Node for Wireless Data Collection with DataSure 4.0
3900BSCU	62447	USB Output Smart Cable
3900BSCM	62449	Gage Mux Smart Cable
3900BSCKB	62448	USB Keyboard Output Smart Cable