

# Mitutoyo

Mitutoyo Quality

## Non-rotating Spindle Type Digital Micrometer Quickmike

Small Tool Instruments  
and Data Management

COOLANT PROOF™ IP65



*1 revolution of thimble feeds the non-rotating spindle*

**10 mm!**



Thimble 1 revolution



1.888.610.7664



[www.calcert.com](http://www.calcert.com)

[sales@calcert.com](mailto:sales@calcert.com)

Catalog No. E12042

Quickmike's evolution to easier and speedier measurement!

# Quickmike

**MeasurLink<sup>®</sup> ENABLED**

Data Management Software by Mitutoyo

Products equipped with the measurement data output function can be connected to the measurement data network system MeasurLink



293-666-20



293-668-20



## Quick measurement

## 20 times faster feed rate

The Quickmike provides a speedy spindle feed of 10 mm per thimble rotation that enables widely differently sized features to be measured quickly. Also, 30 mm of wide measuring range, which is 5 mm longer than the standard type, allows measurement of multiple workpieces.



## Protection level upgraded from IP54 to IP65

Resistant to oil, water, and dust ingress. Useful on the shop floor where coolant may splash on the micrometer.

## COOLANT PROOF™ IP65

COOLANT PROOF is the universal term for Mitutoyo Digimatic Small Tool Instruments that are not only resistant to dust and water ingress but also to deterioration due to contact with the cutting oil or coolant fluids\*1 in normal use.

\*1: Some types of aggressive cutting oil or coolant may degrade the sealing materials over time.

## Visibility improved

Extra-large LCD digits enable easy reading of measurement values.



## Extended battery life

Low-power electronics have extended the battery life to 5 years in normal use\*2.

1.888.610.7664




www.calcert.com

## Absolute scale


The ABS (absolute) linear scale eliminates the need for origin point setting at every power-on and achieves high reliability while being free from overspeed error.

## ABSOLUTE™



## Function locking prevents misoperation!

Function lock enhances usability by preventing the origin from being accidentally changed during measurement.



## Minimum-value hold function ensures measurement value is retained!

The micrometer spindle can be retracted from the workpiece while the measurement value is retained in the display until cleared.




## Battery cap can be easily opened

The groove in the battery cap has been increased from 1.8 mm to 2.4 mm in width to enable the cap to be more easily opened.




Conventional model



308791

New model



04AAC124

1.8 mm

2.4 mm

sales@calcert.com

# Standard Micrometers

Mitutoyo

## Specifications


Metric							
Order No.	Range	Accuracy*	Flatness	Parallelism	Constant-force device	Mass	Output function
293-666-20	0 - 30 mm	$\pm 2 \mu\text{m}$				275 g	
293-667-20	25 - 55 mm	$\pm 2 \mu\text{m}$	0.3 $\mu\text{m}$	2 $\mu\text{m}$	Yes	340 g	
293-668-20	50 - 80 mm	$\pm 3 \mu\text{m}$				480 g	
293-669-20	75 - 105 mm	$\pm 3 \mu\text{m}$		3 $\mu\text{m}$		585 g	Yes

\* Excluding quantizing error of  $\pm 1$  count

Inch/Metric							
Order No.	Range	Accuracy*	Flatness	Parallelism	Constant-force device	Mass	Output function
293-676-20	0 - 1.2 in	$\pm 0.0001$ in				275 g	
293-677-20	1 - 2.2 in	$\pm 0.0001$ in				340 g	
293-678-20	2 - 3.2 in	$\pm 0.0001$ in	0.000012 in		Yes	480 g	
293-679-20	3 - 4.2 in	$\pm 0.0001$ in				585 g	Yes

\* Excluding quantizing error of  $\pm 1$  count

## Dimensions



Unit: mm

Measuring range	L	a	b	c
0 - 30 mm	0	6.2	25	2
25 - 55 mm	25	8.5	36	2.8
50 - 80 mm	50	10.3	47	2.8
75 - 105 mm	75	10.7	60	2.8


## Special-purpose types

### Crimp Height Micrometer



#### Features

- For crimp height measurement of a crimped terminal



#### Specifications


- Range: 0 - 15 mm (342-451-20)
- Accuracy:  $\pm 3 \mu\text{m}$

### Disk Micrometers



#### Features

- For root tangent length measurement of spur and helical gears
- Measurable range of gear pitch: 0.5 to 6 module



#### Specifications


- Ranges: 0 - 30 mm (369-411-20)  
25 - 55 mm (369-412-20)  
0 - 1.2 in (369-421-20)  
1 - 2.2 in (369-422-20)
- Accuracy:  $\pm 4 \mu\text{m} / \pm 0.0002$  in
- Parallelism: 4  $\mu\text{m} / 0.0002$  in
- Flatness: 1  $\mu\text{m} / 0.00004$  in

### Blade Micrometers



#### Features

- Blade type anvil and spindle for measuring narrow-groove diameters and similar features of round workpieces



#### Specifications

- Ranges: 0 - 30 mm (422-411-20)  
25 - 55 mm (422-412-20)  
0 - 1.2 in (422-421-20)  
1 - 2.2 in (422-422-20)
- Accuracy:  $\pm 3 \mu\text{m} / \pm 0.00015$  in
- Parallelism: 3  $\mu\text{m} / 0.00015$  in

#### Common specifications


- Preset
  - Resolution: 0.001 mm
  - Quantizing error:  $\pm 1$  count
  - Protection level: IP65\*
  - Power supply: Silver oxide button cell battery SR44
  - Battery life: Approx. 5 years under normal use
  - Output: Measurement Data
  - Operating temperature: 5 to 40°C
  - Storage temperature: -10 to 60°C
  - Standard accessories: Silver oxide button cell battery SR44 (9038882), 1 pc. supplied for testing purposes only.
- Setting standard (excluding 0-15/30 mm and 0-1 inch range models)

#### Common functions

- Preset
- (ABS measurement system)
- Zero-setting
- (INC measurement system)
- Hold
- Function lock
- Auto power off
- Measurement Data output
- Error alarm
- Minimum value hold

#### Optional accessories

- Connecting cable to DP-1VA LOGGER  
1 m: 05CZA662  
2 m: 05CZA663  
Note: Water-proof type which is not compatible with standard Digimatic micrometers.
- Digimatic mini processor DP-1VA LOGGER: 264-505
- Connection with PC (wired communication): USB Input Tool Direct USB-ITN-B (2 m): 06AFM380B
- Connection with PC (wireless communication): Connecting cable to U-WAVE-T (160 mm): 02AZD790B  
Cable for foot switch: 02AZE140B



**Whatever your challenges are,  
Mitutoyo supports you from start to finish.**

Mitutoyo is not only a manufacturer of top quality measuring products but one that also offers qualified support for the lifetime of the equipment, backed up by comprehensive services that ensure your staff can make the very best use of the investment.

Apart from the basics of calibration and repair, Mitutoyo offers product and metrology training, as well as IT support for the sophisticated software used in modern measuring technology. We can also design, build, test and deliver bespoke measuring solutions and even, if deemed cost-effective, take your critical measurement challenges in-house on a sub-contract basis.



**Find additional product literature  
and our product catalogue**

<http://www.mitutoyo.co.jp/global.html>

Our products are classified as regulated items under Japanese Foreign Exchange and Foreign Trade Law. Please consult us in advance if you wish to export our products to any other country. If the purchased product is exported, even though it is not a regulated item (Catch-All controls item), the customer service available for that product may be affected. If you have any questions, please consult your local Mitutoyo sales office.

Note: Product illustrations are without obligation. Product descriptions, in particular any and all technical specifications, are only binding when explicitly agreed upon.

MITUTOYO and MiCAT are either registered trademarks or trademarks of Mitutoyo Corp. in Japan and/or other countries/regions. Other product, company and brand names mentioned herein are for identification purposes only and may be the trademarks of their respective holders.

# Mitutoyo

**Mitutoyo Corporation**

20-1, Sakado 1-Chome,  
Takatsu-ku, Kawasaki-shi,  
Kanagawa 213-8533, Japan

T +81 (0) 44 813-8230

F +81 (0) 44 813-8231

<http://www.mitutoyo.co.jp>

**1.888.610.7664**



**www.calcert.com**

**sales@calcert.com**