

Flame-Retardant Storage

For added protection when welding and grinding in the field, Klein's Flame-Retardant pouches meet the performance requirements of NFPA-701. The pouches have strong bottoms and feature a convenient tunnel loop for sliding over your belt.

- #4 Flame-Retardant Canvas.

Cat. No.	UPC Code 0-92644+	Belt Capacity	Belt Connection	Length	Width
Flame-Retardant Canvas Bolt Bag					
5416TFR	55529-9	up to 3" (76 mm) wide	Tunnel	5" (127 mm)	9" (229 mm)
Cat. No.	UPC Code 0-92644+	Back Depth	Diameter	Front Depth	Width
Flame-Retardant Electrode Bag					
5471FR	55530-5	15-1/2" (394 mm)	2-1/2" (64 mm)	12" (305 mm)	N/A



5416TFR



5471FR

FR

Connecting Bar Lock Collar and Holder

Keep your connecting bar safely close at hand. The lock collar (Cat. No. 5459C) slides securely over the connecting bar to lock it safely into the specially designed holder (Cat. No. 5459SLVR) that can be attached to a tool belt up to 3-1/2" (89 mm) wide.

- Lock collar can be fitted to Klein Tools 7/8" round hex connecting bars. (Cat. No. 3248 and 3246)

Cat. No	UPC Code 0-92644+	Description	Belt Connection	Belt Capacity
5459C	55532-9	Connecting Bar Lock Collar	N/A	N/A
5459SLVR	55531-2	Connecting Bar Holder with Lock Collar	Tunnel	up to 3-1/2" (89 mm) wide



5459SLVR



5459C

⚠ WARNING: Lock Collar should ONLY be used on Klein 7/8" Connecting Bars. Lock Collar must be installed on connecting bar before using holder.

