



## REUSABLE FACE MASK INSTRUCTIONS

60442

ENGLISH

KEEP THESE INSTRUCTIONS FOR FUTURE REFERENCE

### GENERAL SPECIFICATIONS

#### STANDARDS

The Replaceable Filter (60443) is part of the approved assembly.

#### APPLICATIONS

The Reusable Face Mask 60442 is for basic protection against household dust, such as pollen, dander, non-toxic dust, and common airborne irritants.

### WARNINGS

*For correct use of the mask and filters, you must read and understand the instructions before starting work. You must comply with all limitations and warnings. Failure to follow instructions and misuse of the product may result in sickness or death.*

- **ALWAYS** conduct a mask inspection prior to each use to ensure mask is in proper, usable order.
- Not NIOSH-approved
- **SILICA: DO NOT** use this mask for protection against the inhalation of silica.
- **ASBESTOS: DO NOT** use this mask for protection against the inhalation of asbestos.
- **MOLD: DO NOT** use this mask for protection against the inhalation of mold.
- **NON-ORGANIC CHEMICALS: DO NOT** use this mask for protection against the inhalation of non-organic chemicals.
- **NOT A MEDICAL DEVICE. DO NOT** use this mask for protection against airborne pathogens.
- **WILL NOT** prevent transmission of airborne pathogens.
- **NOT FOR USE** in atmospheres immediately dangerous to life or health. Use in a well-ventilated area and not in a confined space.
- **NEVER** substitute, modify, add or omit parts. Use only exact replacement parts in the configuration as specified in User Instructions

#### Leave the work area immediately if:

- Dizziness or distress is experienced
- Breathing becomes difficult
- A defect is discovered in the dust mask

### FITTING (FIG. 1, 2, 3, 4)

The mask must be inspected by the wearer before and after each use to ensure that it is in good working condition and valves and filters are seated correctly. Remove eyewear (if worn). If facial hair goes beyond the border of the mask an effective seal will not be achieved

**STEP 1 (FIG. 1):** Grasp the bottom mask straps with each hand and securely hook and loop them together behind your neck.

**STEP 2 (FIG. 2):** Lift the upper headband over the crown of your head to support the mask.

**STEP 3 (FIG. 3):** Adjust neck hook and loop strap and headband sliding adjustment to provide a tight, comfort fit to prevent air leakage between mask and face.

**STEP 4 (FIG. 4):** Adjust the nose piece to the contours of your face/nose, to reduce air leakage between mask and minimize glasses fogging.

### CLEANING

#### DO NOT WASH FILTERS.

- Remove the filter while cleaning.
- Clean the mask shell with a soft cloth dampened with mild soapy water (no solvents).

### FILTER INSPECTION & REPLACEMENT

Filters should be changed once a month or more frequently if you find a resistance to breathing.

A maintenance record should be kept of these filter changes.

See #60443 Filter Instructions for replacing filters.

Expiration date: Filters must be discarded 5 years after manufacture date.

|  |                                |  |   |
|--|--------------------------------|--|---|
|  | Read instructions before using |  | Temperature range of storage conditions |
|  | Expiration date                |  | Humidity range of storage conditions    |

### STORAGE

The mask should be stored out of direct sunlight, away from sources of high temperature, and in an uncontaminated environment. Spare filters should also be stored in a cool dry atmosphere at a temperature of between 14°F (-10°C) and 104°F (40°C). Store in the bag provided when not in use. Storage under conditions other than those specified may affect service life.

FIG. 1



FIG. 2



FIG. 3




FIG. 4

