

VOLTAGE/CONTINUITY TESTERS

MEASURE/INDICATE AC/DC VOLTAGE

- Two new Voltage/Continuity Testers for 2021
- cULus Listed (all models)
- CAT IV 600V & CAT III 600V options
- Digital Multifunction, Analog and Solenoid Models
- IP42 Dustproof/Water (61-557 & 61-547)
- 2 Meter drop protection (61-557 & 61-547)
- Lead holders are spaced to test tamper resistant outlets
- Bright LED flashlight, continuity, NCVT, GFCI test, LoZ (61-557)



61-557

Voltage & Continuity Tester
w/LCD, GFCI, Flashlight & NCVT
CAT IV 600V



61-076

Voltage & Continuity Tester
5-600V
CAT III 600V



61-547

8 Range AC/DC Voltage Indicator
w/Polarity Indicator
CAT III 600V



61-065

Voltage Tester
5-600V
CAT III 600V



Probe Holder for Storage/Measurement (61-557, 61-547)



THE ELECTRICIAN'S
CHAMPION™ **IDEAL**®



1.888.610.7664

 www.calcert.com

sales@calcert.com

VOLTAGE/CONTINUITY TESTERS AND VOLTAGE TESTERS

VOLTAGE TESTER SELECTION GUIDE FOUR NEW NCVTS FOR 2021				
	61-557	61-547	61-076	61-065
FEATURES				
CAT Rating (Safety)	CAT IV 600V	CAT III 600V	CAT III 600V	CAT III 600V
Listing Preferred	cULus, CE	cULus, CE	cULus	cULus
Drop Protection	6.6 ft. (2m)	6.6 ft. (2m)		
Ingress Protection	IP42	IP42	—	—
AC Voltage (Volts)	6 ~ 600	24 ~ 600	5 ~ 600	100 ~ 600
DC Voltage (Volts)	6 ~ 600	12 ~ 600	5 ~ 600	100 ~ 600
High Voltage Alarm	ACV >36 or DCV >50V	ACV/DCV >48V	—	—
Audible Continuity	✓	—	—	—
Visual Continuity	✓	—	✓	—
Backlight	✓	—	—	—
Low Impedance (LoZ)	✓	—	✓	✓
NCV	90-600V AC	—	—	—
Auto Ranging	✓	—	—	—
Magnetic Strap Mount	✓	✓	—	—
Test Probe Holder	✓	✓	✓	✓
Flashlight	✓	—	—	—
Auto-Power Off (APO)	✓	—	—	—
Low Battery Indicator	✓	—	—	—
Battery Type (included)	3 x 1.5V AAA	—	4 x 1.5V LR44	—
LCD Display Count	600	—	—	—
Backlight	✓	—	—	—
DC Polarity Indication	✓	✓	✓	—
Leads	Removable	Fixed	Removable	Removable
GFCI Test	✓	—	—	—
Display	LCD	Neon Lamps	Indicator Movement	Indicator Movement
Warranty	2-Year*	2-Year*	2-Year*	2-Year*
ACCESSORIES				
Test Leads (included)	TL-757	—	61-070	61-070
Magnetic Hanging Strap (sold separately)	UMHS-757	UMHS-757	—	—



Probe Holders
are spaced to
test tamper
resistant
outlets
(61-557 & 61-547)

**Continuity
Testing**
(61-557 &
61-076)

**Backlit Display
and Flashlight**
(61-557)

NCVT
in tip detects
presence of
AC voltage
(61-557)

Tests GFCI
protected
circuits
(61-557)

LoZ
option to
eliminate ghost
voltage
(61-557)



IDEAL INDUSTRIES, INC.