



FlexShaft™ Machines

Clears From 1¼" to 4" Drain Line



RIDGID FlexShaft machines are lightweight, compact and highly efficient machines that deliver wall-to-wall clean in 1¼" to 4" drain lines up to 70'. FlexShaft machines can also be operated while an inspection camera is in the line, letting you see while you clean. No other soft blockage expert can do that.

- **Wall-To-Wall Clean:** Chain knockers expand for full pipe cleaning
- **Simultaneous Camera Use:** FlexShaft machines let you keep your camera in-pipe while you work
- **Increase Productivity:** Faster setup and cleanup, quick cleaning, and cordless convenience for additional time savings
- **Customize Your Machine:** A full range of chain knockers and accessories are available

RIDGID® FlexShaft machines utilize specialized chain knockers attached to a flexible cable that are spun at high speeds by a cordless drill attached to the center drive shaft. Since the cable spins inside a durable nylon sheath that is housed within a fully contained drum, there is less jobsite mess.



SPECIFICATIONS

| Model | K9-102 | K9-204 |
|------------------------------------|--|---|
| Drain Capacity (Nom.) | 1 1/4" to 2" (32 – 50 mm) | 2" to 4" (50 – 100 mm) |
| Cable Diameter (without Sheath) | 1/4" (6 mm) | 5/16" (8mm) |
| Cable Assy. Diameter (with Sheath) | 3/8" (9,5 mm) | 1/2" (12,7 mm) |
| Cable Assembly Length | 50' (15,2 m) | 70' (21,3 m) |
| Rotational Speed | Maximum 2500 RPM | Maximum 2500 RPM |
| Drill Attachment | 5/16" Hex (8 mm) | 5/16" Hex (8 mm) |
| Weight (without Drill/Knocker) | 24.3 lbs. (11,0 kg) | 37.3 lbs. (16,9 kg) |
| Dimension (without Drill) | 19.2" x 7.5" x 22.1" (488 mm x 191 mm x 562 mm) | 21.1" x 10.8" x 24.2" (536 mm x 274 mm x 615 mm) |
| Operating temperature | 20°F to 140°F (-6°C to 60°C) | 20°F to 140°F (-6°C to 60°C) |

ORDER INFORMATION

| CATALOG NO. | MODEL NO. | DESCRIPTION | WEIGHT (lb.) (kg) | |
|-------------|-----------|---|----------------------|------|
| 64263 | K9-102 NA | FlexShaft, 1 1/4" - 2" Pipes Includes: 50' 1/4" cable and kit* | 29.5 | 13,4 |
| 64273 | K9-204 NA | FlexShaft, 2" - 4" Pipes Includes: 70' 5/16" cable and kit** | 43.5 | 19,7 |

* K9-102 includes: K9-102 1 1/4" & K9-102 2" Knockers, FlexShaft 4 oz Lubricant, PVC 1 1/4" & PVC 1 1/2" Attachments, Hex Key 4 mm T-handle Tool, Hex Key 3 mm T-handle Tool, RIDGID Tool Bag, K9-102 & K9-204 Manual Pack, Sheath Stock.

** K9-204 includes: K9-204 2" & K9-204 4" Knockers, FlexShaft 4 oz Lubricant, Hex Key 4 mm T-handle Tool, Hex Key 3 mm T-handle Tool, RIDGID Tool Bag, K9-102 & K9-204 Manual Pack, Sheath Stock.



Chain Knockers

• All pipe types

• For soft blockages and grease

ACCESSORIES

| CATALOG NO. | DESCRIPTION |
|-------------|--|
| 64283 | FlexShaft Knocker, 1/4" cable, 1 1/4"-2" pipe, single chain, carbide tip |
| 64288 | FlexShaft Knocker, 1/4" cable, 2" pipe, 2 chain, carbide tip |
| 64293 | FlexShaft Knocker, 1/4" cable, 1 1/4"-2" pipe, single chain |
| 64298 | FlexShaft Knocker, 1/4" cable, 2" pipe, 2 chain |
| 64308 | FlexShaft Knocker, 5/16" cable, 2" pipe, 2 chain, carbide tip |
| 64313 | FlexShaft Knocker, 5/16" cable, 3" pipe, 3 chain, carbide tip |
| 64318 | FlexShaft Knocker, 5/16" cable, 4" pipe, 3 chain, carbide tip |
| 64323 | FlexShaft Knocker, 5/16" cable, 2" pipe, 2 chain |
| 64328 | FlexShaft Knocker, 5/16" cable, 3" pipe, 3 chain |
| 64333 | FlexShaft Knocker, 5/16" cable, 4" pipe, 3 chain |
| 64338 | RIDGID FlexShaft Lubricant, 8 oz |
| 64343 | FlexShaft 1/4" Assembly, 50' cable, sheath, couplings |
| 64348 | FlexShaft 5/16" Assembly, 70' cable, sheath, couplings |
| 64363 | RIDGID Modified Wallpipe 1 1/4" |
| 64368 | RIDGID Modified Wallpipe 1 1/2" |
| 64643 | FlexShaft 1/4" Sheath Stock, 12" |
| 64648 | FlexShaft 5/16" Sheath Stock, 12" |



Carbide Tipped Chain Knockers

• Hard walled pipes

• For soft blockages, grease, scale and roots



All sales subject to Ridge Tool Company Terms and Conditions of Sales. Catalog Sheet No. R-19-C (319) Effective Date: May 1, 2019
©2019 RIDGID, Inc. The Emerson logo and RIDGID logo are registered trademarks of Emerson Electric Co. or RIDGID, Inc. in the U.S. and other countries.