



Compact Series Camera Reels Compact2, C40 and M40



RIDGID® SeeSnake® Compact series camera reels deliver big performance in a small package. Choose from three models to handle a wide range of demanding inspections. Compatible with the new SeeSnake CS6x Versa digital reporting monitor for fast set-up and easy viewing, while built-in Wi-Fi and Bluetooth make live streaming and inspection to an iOS™ or Android™ device simple with the free HQx Live app.

- 25 mm self-leveling camera head provides a crisp image that is always upright
- TruSense™ technology features two-way communication between the camera and a CSx series Wi-Fi enabled monitor*
- High dynamic range image sensor provides bright, saturated images with improved detail, even in difficult lighting conditions*
- TiltSense inclinometer lets you know camera's degree of tilt inside the pipe when used with a CSx series monitor*
- Equipped with high power FleXmitter® 512 Hz sonde which is compatible with all RIDGID locators
- Download the free HQx Live app to view and record inspection jobs on your phone or tablet
- Use with the SeeSnake CS6x Versa to create the optimal viewing angle and for fast, efficient job setup







SPECIFICATIONS

- Light Source High-Intensity LED
- Push Cable Length..... 100' (30 m)/131' (40 m)
- Push Cable Minimum Bend Radius..... 2.5" (64 mm)
- 512 Hz Sonde High-power Flexmitter®
- Dimensions (LxWxH) 25" x 14" x 17"
(626 mm x 360 mm x 429 mm)
- Operating Temperature 14°F to 122°F (-10°C to 50°C)
- Storage Temperature..... 14°F to 158°F (-10°C to 70°C)
- Ingress Protection (without Monitor)..... IPx6

COMPACT SERIES QUICK COMPARISON GUIDE

| CAMERA REEL | | CAMERA HEAD | PUSH CABLE | MINIMUM BEND RADIUS | LINE CAPACITY |
|-------------------------|---|--|--------------|---------------------|----------------------------|
| Compact2 Camera Reel | | 25 mm (1") Self-Leveling | 100' (30 m) | 2.5" (64 mm) | 1.5" - 6" (38 mm - 152 mm) |
| Compact C40 Camera Reel |  | 25 mm (1") Self-Leveling w/TruSense Technology | 131' (40 m) | 2.5" (64 mm) | 1.5" - 6" (38 mm - 152 mm) |
| Compact M40 Camera Reel |  | 25 mm (1") Self-Leveling w/TruSense Technology | 131' (40 m) | 3" (76 mm) | 1.5" - 8" (38 mm - 203 mm) |

ORDER INFORMATION

| CATALOG NO. | DESCRIPTION | WEIGHT (lb.) | (kg) |
|-------------|---|--------------|------|
| 48093 | Compact2 (Reel Only) | 17.0 | 7.7 |
| 65098 | Compact2 w/CS6x Versa Monitor | 21.9 | 9.9 |
| 65103 | Compact2 w/CS6x Versa Monitor, Battery and Charger | 24.9 | 11.3 |
| 63668 | Compact C40 (Reel Only) | 17.2 | 7.8 |
| 63823 | Compact C40 w/CS6x Versa Monitor | 22.1 | 10.0 |
| 63828 | Compact C40 w/CS6x Versa Monitor, Battery and Charger | 25.1 | 11.4 |
| 63673 | Compact M40 (Reel Only) | 22.0 | 9.8 |
| 63813 | Compact M40 w/CS6x Versa Monitor | 26.9 | 12.0 |
| 63818 | Compact M40 w/CS6x Versa Monitor, Battery and Charger | 29.9 | 13.6 |

ACCESSORIES

| CATALOG NO. | DESCRIPTION |
|-------------|---|
| 47793 | 36 mm Pipe Guide, 25 mm Camera, Pkg of 1 |
| 35338 | 45 mm Pipe Guide, 25 mm Camera, Pkg of 2 |
| 97462 | 60 mm Pipe Guide, 25 mm Camera, Pkg of 6 |
| 46708 | 85 mm Pipe Guide, 25 mm Camera, Pkg of 2 |
| 46713 | 125 mm Pipe Guide, 25 mm Camera, Pkg of 2 |
| 63868 | Various Pipe Guides, 25 mm Camera Head |
| 17553 | Spanner Wrench, 25 mm |



HDR

High Dynamic Range (HDR) image sensor offers clear in-pipe imaging..



TiltSense™

Data Sensor displays camera's angle in pipe.



Scan for more information on HQx Live

