FlexShaft k9-306



RANGE OF ACCESSORIES



CHOOSING THE RIGHT ACCESSORY

RIDGID® FlexShaft® Machines utilize specialized accessories attached to a flexible cable that are spun at high speeds for effective wall-to-wall cleaning action. Selecting the correct chain knocker or brush for your application and pipe material will ensure an efficient clean-out.

CLEANING V. CLEARING

Chain knockers deliver wall-to-wall clean and can get pipes working like new, creating opportunities for warranties or up charges. Total cleaning also lets you prepare damaged pipe for relining as an alternative to digging and replacing.

MAINTENANCE AND RELINING

EMERGENCY BLOCKAGES

When an emergency blockage needs to be cleared to get water running and the client doesn't want to pay for total pipe cleaning, just clearing the blockage is also a solution.

PIPE WALL CLEANING

CHAIN KNOCKERS



SMOOTH CHAIN Knockers

- For all pipe types
- For soft blockages and grease



CARBIDE TIPPED CHAIN KNOCKERS

- For hard-walled pipes
- For scale, roots, grease and soft blockages



PENETRATING, CARBIDE TIPPED CHAIN KNOCKERS

- For hard-walled pipes
- For wipes, scale, roots and soft blockages

BRUSHES





- Gentle cleaning of fragile pipes
- Centering guide for other tools
- For spreading resin when spray lining
- For final cleanup to sweep fine debris downstream



NYLON-STEEL BRUSH

- For cleaning & light grinding
- For relining preparation of PVC & cast iron pipes
- For final cleanup to sweep fine debris downstream

PENETRATING TIP



PENETRATING TIP

 Penetrating tip functionality with smooth chains when carbide tipped chains are too aggressive



FlexShaft® K9-306

FLEX YOUR COVERAGE.

FIND THE RIGHT CHAIN KNOCKER ID HEAD ACCESSORIES FOR THE JOB TO GET WALL-TO-WALL CLEAN

Use the table below for recommended options based on blockage, pipe size and pipe type.



		K9-306 MACHINE									
								Ø		Ø	
		Chain Knockers			Carbide	Tipped Chain I	Knockers -	l	Penetrating Head Chain Knockers		
	CATALOG NO.	66618	66623	66628	66633	66638	66643	66648	66653	66658	71858
	DESCRIPTION	K9-306 3"	K9-306 4"	K9-306 6"	K9-306 3" CARBIDE	K9-306 4" CARBIDE	K9-306 6" CARBIDE	K9-306 - 3" PENETRATING HEAD	K9-306 - 4" PENETRATING HEAD	K9-306 - 6" PENETRATING HEAD	K9-306 PENETRATING TIP
	PIPE SIZE (inch / mm)	3"- 4" (76-102 mm)	4"-5" (102-127 mm)	5"- 6" (127-152 mm)	3"- 4" (76-102 mm)	4"-5" (102-127 mm)	5"- 6" (127-152 mm)	3"- 4" (76-102 mm)	4"-5" (102- 127 mm)	5"- 6" (127-152 mm)	6" (150 mm)
	COPPER				⊘	⊘	⊗	⊗	⊘	∅	⊘
	GALVANIZED				0	⊘	⊘	⊗		0	⊘
	CAST IRON				0	⊘	⊘	⊗	⊘	Ø	⊗
PIPE TYPE	PVC	⊘	∅	0							
PIPE	ABS	⊘	⊘	\odot							⊘
	ORANGEBURG	⊘	∅	⊘							∅
	CORRUGATED	⊘	⊘	(O							
	CLAY	⊘		⊘							Ø
	GREASE	⊘	⊘	⊘	⊘	9	⊘			0	⊗
	SOFT BLOCKAGE	⊘	⊘		⊘	⊘	⊘			∅	⊘
BLOCKAGE	SCALING				⊘	⊘	⊘			0	
<u>m</u>	ROOTS				⊘	0	⊘		∅	Ø	
	WIPES								∅	Ø	⊘
	INCLUDED WITH KIT		Ø	⊘							

Any accessory can be purchased separately.





FlexShaft® K9-306 FIND THE RIGHT BRUSH TO CLEAN AND PREPARE DRAINS WALL-TO-WALL

K9-306 MACHINE			K9-306 MACHINE								
				NYLON BRUSH		N N	YLON AND STEEL BRU	SH			
APPLICATION			Suitable as a cer	or gentle cleaning of f ntering guide for othe ading resin when spra	rtools	 Nylon – Steel material for cleaning & light grinding Suitable for relining preparation of PVC and cast iron pipes 					
	CATALOG NO.		68958	68963	68968	68988	68993	68998			
	PIPE SIZE (inch / mm)		3" (75 mm)	4" (100 mm)	6" (150 mm)	3" (75 mm)	4" (100 mm)	6" (150 mm)			
		COPPER		⊘		⊗					
		GALVANIZED		⊘		⊗					
		CAST IRON		⊘		⊗					
CHING	RIAL	PVC		\odot		⊗					
BRUSH MATCHING	PIPE MATERIAL	ABS		⊘		⊗					
BRUS		ORANGEBURG		⊘							
		CORRUGATED		⊘							
		CLAY		\odot							
		PORCELAIN		⊘							
	BRUSH DIAMETER (inch / mm)		3" (75 mm)	4" (105 mm)*	6" (155 mm)*	3" (75 mm)	4" (105 mm)*	6" (155 mm)*			
	CABLE DIAMETER (mm)		10	10	10	10	10	10			
SECURING RING MATCHING	CATALO	G NO.		68928		68928					

*4" and 6" nylon - steel brushes need to have longer strings in order to provide a thorough cleaning



