



Conductive Chair Mat


Maintenance:

To keep vinyl clean and avoid insulative electrical readings, use a neutral cleaner such as ACL's 4030 Neutral Cleaner ready-to-use formula. The low alcohol, high surfactant formula will clean deeply without damaging the structural integrity of the conductive material. Runners can be cut easily with a utility knife.

Warranty:

ACL Inc. offers an exclusive lifetime warranty on the electrical resistance properties of the mat (10^3 – 10^6 ohms). If the electrical properties should fail (when tested to ANSI/ESD S20.20) during the lifetime of an ACL mat due to manufacturing or physical defects, we will replace the mat free of charge.

This warranty does not apply to mats that are abused, improperly used, or cleaned with mat cleaners not tested and approved by ACL, Inc.



Conductive Chair Mat

6800: 46" x 50" (10.25 lbs)

Conductive Floor Runner


6836: 36" x 75' (180 lbs)

6848: 48" x 75' (240 lbs)



FEATURES:

- ❖ Stippled surface; 0.090" (2.29 mm) thickness
- ❖ Resistance: 10^3 - 10^6 ohms per ANSI/ESD S7.1-2005
- ❖ Compliant to ANSI/ESD S20.20
- ❖ Passes weathering ozone resistance per ASTM D178-01
- ❖ Hardness: 90 +/- 5 shore A per ASTM D2240
- ❖ Electricals are warranted for lifetime of mat
- ❖ UV additives protect color and eliminate fading
- ❖ Runners may be cut with utility knife
- ❖ Available in black only
- ❖ Recyclable
- ❖ Made in U.S.A.



ACL Inc. registered to
ISO-9001 : 2015
Certificate No. 10002746