


Signal Splitter/Repeater with double outputs for mA and V signals

The Signal Splitter/Repeater IspPAQ-632 is used for isolation, conversion and distribution of 0/4 ... 20 mA, 0/1 ... 5 V and 0/2 ... 10 V standard signals. The measuring input can also supply the loop power for 2-wire transmitters.

The input and two isolated outputs can be easily configured by using DIP switch. Due to the calibrated range selection no further adjustment is necessary.

The auxiliary power can be supplied via the connection terminals or via the optional In-Rail-Bus connector. A green LED on the front of the unit has been provided to monitor the power supply.



- Calibrated signal setting via DIP switch**
Input and outputs can be set by using DIP switch – high precision without any further adjustment
- 4-Port isolation**
Protection against erroneous measurements due to parasitic voltages or ground loops
- Extremely slim design**
6.2 mm slim housing for a simple and space saving DIN rail mounting
- Optional In-Rail-Bus mounting rail connector**
allows for fast and economical installation
- Protective Separation acc. to EN 61140**
Protects service personnel and downstream devices against impermissibly high voltage
- Maximum reliability**
No maintenance costs


Specifications:

Input					
Input signal (calibrated switchable)	0... 20 mA 4... 20 mA	0... 10 V 2... 10 V	0... 5 V 1... 5 V		
Input resistance	Current input Voltage input	≤ 35 Ω ≥ 100 kΩ			
Overload	Current input Voltage input	< 50 mA < 30 V			
Transmitter supply Tx (switchable)	16 V (open circuit voltage/short circuit current ≤ 22 V/35 mA)				
Output I / Output II					
Output signal (calibrated switchable)	0... 20 mA 4... 20 mA	0... 10 V 2... 10 V	0... 5 V 1... 5 V		
Load	Current output: ≤ 6 V (300 Ω at 20 mA)		Voltage output: ≤ 5 mA (2 kΩ at 10 V)		
Linear transmission range	-1 ... +110 %				
Residual ripple	< 10 mV _{rms}				
General Data					
Transmission error	< 0.1 % full scale				
Temperature coefficient ¹⁾	< 100 ppm/K				
Cut-off frequency -3 dB	5 kHz				
Response time T ₉₉	150 μs				
Test voltage	3 kV AC, 50 Hz, 1 min. Input against Output 1 against Output 2 against power supply				
Working voltage ²⁾ (Basic Insulation)	600 V AC/DC for overvoltage category II and pollution degree 2 acc. to EN 61010-1				
Protection against electrical shock ²⁾	Protective separation according to EN 61140 by reinforced insulation in accordance with EN 61010-1 up to 300 V AC/DC for overvoltage category II and pollution degree 2 between all circuits				
Ambient temperature	Operation	-25°C to +70°C (-13 to +158°F)			
	Transport and storage	-40°C to +85°C (-40 to +185°F)			
Power supply	24 V DC	voltage range 16.8 ... 31.2 V DC, approx. 1.4 W			
EMC ³⁾	EN 61326-1				
Construction	6.2 mm (0.244") housing, protection class IP 20, mounting on 35 mm DIN rail acc. to EN 60715				
Weight	Approx. 70 g				

1) Average TC related to full scale value in specified operating temperature range, reference temperature 23 °C

2) For applications with high working voltages, ensure there is sufficient spacing or isolation from neighboring devices and protection against electric shocks.

3) Minor deviations possible during interference

Block diagram/Connections**Dimensions**