



715 High CO & NOX Combustion Analyzer

New! Four Tools in One!!

The TPI 715 is an all in one instrument designed to maximize diagnostic efficiency and accuracy.

Ask about
the optional
A740
Infrared
Printer.

Turn over for
technical
information
and accessory
part numbers.

NOTE: When selecting oil as fuel be sure to use the optional oil filter or reading could become erratic. Order item A773.

The
Value
Leader™



4.0"w x 8.12"h x 2.25"d

715 Four Units in One

1. Combustion Efficiency Analyzer

- Measure O₂, CO, and NO
- Calculate CO₂, NOX, efficiency, excess and air ratio
- Will work with high efficiency furnaces, hot water heaters, and other combustible gas appliances.

2. NO & NOX Analyzer

- Measure 0 ~ 5,000ppm NO
- Calculate 0 ~ 5, 250ppm NOX

3. CO Analyzer

- Measure 0-10% CO

4. Differential Thermometer

- Dual input K-type thermocouple temperature tester

NOTE: If you are working in the oil and gas industry or tuning compression engines you must use TPI's 715K3 kit.

3-YEAR
LIMITED
WARRANTY



715 FEATURES

- Easy to use
- Large, easy-to-use display
- Print real-time or stored readings, Save 10 sets of data
- 12V car power adapter
- IR printer port
- Protective rubber boot included

715 ACCESSORIES

CO Sensor, Oxygen Sensor, NO Sensor
Protective Boot, Stack Probe, PVC Tubing,
Water/filter trap on Stack Probe, Shoulder
Strap Carrying Case, Spare Particle Filters,
Rechargeable Batteries

715 OPTIONAL ACCESSORIES

A740 IR Printer

A767 IRDA Adapter for Data Logging

A773 Sulfur Filter for Oil

A740 Infrared Printer

- Easy to use
- Battery operated
- Self test facility
- Adjustable contrast
- Manual paper feed
- Maximum transmitting distance 16"(45cm)
- Compatible with most other combustion analyzers



3.0"w
x 6.0 h
x 1.75"d

3-YEAR
LIMITED
WARRANTY





TECHNICAL SPECIFICATIONS AND ACCESSORIES

- Digital Multimeters
- Clamp Meters
- Hand-held Oscilloscopes
- Refrigerant & Combustible Gas Leak Detectors
- Temperature Testers
- BNC Coax Cable Connectors
- Test Leads
- Accessories

**Test Products
International, Inc.**

715 HIGH CO & NOX ANALYZER

Temperature Measurement

Range	-50° to 1832°F, or -50° to 1,000°C
Resolution	1°F or C
Accuracy (K-type)	±0.3% of Full Scale

Nitric Oxide Measurement

Range	0 to 5,000ppm
Resolution	1ppm
Accuracy	<100ppm: ±5ppm <1000ppm ±5% >1000ppm: ±10%

NOX Measurement

Range	0 to 5, 250
Resolution	1ppm
Accuracy	Calculated

Gross/Net Efficiency

Range	0 to 100%
Resolution	0.1%
Accuracy	Calculated

Oxygen (O₂) Measurement

Range	0 to 25%
Resolution	0.1%
Accuracy	±0.3%

Carbon Monoxide (CO) Measurement

Range	0 to 9.999%
Resolution	0.0001%
Accuracy	<1.0% CO: ±5% + 5 digits <5.0% CO: ±7% + 5 digits >5.0% CO: ±10% + 5 digits

Carbon Dioxide (CO₂)

Range	0 to 25%
Resolution	0.1%
Accuracy	Calculated

CO/CO₂ Ratio

Range	0 to 0.9999
Resolution	0.0001
Accuracy	Calculated

Instrument Specifications

Operating Temperature Range	14° to 122°F (-10° to 50°C)
Battery	4AA Batteries
Fuels	Natural Gas, LPG, Light Oil, Heavy Oil
Display	Backlit LCD
Data Storage	10 sets of readings
Time & Date	24 Hour Real Time Clock
Dimensions	200mm x 90mm x 60mm
Weight	500g
Switch Off	Failsafe
Exhaust	Safety Spigot
Conforms To:	BS7927 (and the draft BS7967)

ACCESSORIES

Standard

Flue Temperature Probe w/K-type	A742
K-Type Temperature Probe	GK11M
In-Line Filter Complete	A762
Mini Pump Protection Filter Assembly	A763
Rubber Boot	A765
Soft Carrying Case	A768
Exhaust Spigot	A764

Optional

20 Foot Flue Gas Analyzer Probe	A770-20
Infrared Printer	A740

**NOTE: When selecting oil as fuel be sure to use the optional oil filter or reading could become erratic.
Order item A773.**



Distributed By:

L 715-0305
Copyright © 2005 Test Products International, Inc.