

3M™ Slim Lock Closures

3M™ Slim Lock Closures for wireless weatherproofing applications are compact closures that protect RF connections at the antenna and remote radio unit (RRU). Protection of these connections is critical to preventing moisture intrusion, which can lead to signal integrity issues and service disruptions.

As antennas become more densely populated with RF connectors as a result of Multiple In Multiple Out (MIMO) antenna requirements or LTE and the trend toward multi-band multi-service antennas, weatherproofing becomes challenging and time consuming.

Due to its clamshell-like design, the 3M Slim Lock Closure can be installed after the connection is complete at the antenna or RRU. A proprietary, highly compliant sealing gel technology found inside the closure displaces air around the cable and connector, providing a robust sealing interface. The closure can be opened, removed and reinstalled without disconnection of the network, thereby avoiding signal interruptions and replacement costs.



3M™ Slim Lock Closures installed on an antenna

Features	Benefits
Compact design	Fits in small or congested areas
One-handed operation	Fast installation
Easy to install/remove	Intuitive install; minimal training needed
Re-enterable	Allows for PIM/sweep testing
Reusable	No extra supplies needed to re-seal
Tool-less	No additional installation costs and steps

3M™ Slim Lock Closures can also be installed inverted when connectors are located at the top of the antenna and still maintain a tight seal around the connection point.

These closures are re-enterable, re-usable and tool-less, making it a time-saving, cost-effective, easy-to-use solution for the wireless industry, especially where PIM/sweep testing is concerned. They are installed quickly with one hand and can fit in small spaces for fast installation.

3M Slim Lock Closures are available in different sizes to fit different types and sizes of RF connectors with nominal half-inch coaxial cable.



3M™ Slim Lock Closure Family



3M™ Slim Lock Closures can be easily installed with one hand.

Specifications	
Environmental protection	IP68
Operating temperature	-40 to 65°C
Icing/freezing rain tolerance	MIL-STD-810
Blowing rain tolerance	GR-3151-CORE

Ordering information

Product number	Neck size (range)	Typical Connector Application	Cable diameter (range)	3M ID	Min. order
SLC-716	1.00" - 1.03" (25.4 - 26.2 mm)	DIN 716	0.53" – 0.63" (13.5 – 16.0 mm)	80-6113-8755-8	12
SLC-A-MINI	0.68" - 0.78" (17.3 - 19.8 mm)	Mini-DIN	0.53" – 0.63" (13.5 – 16.0 mm)	80-6114-9597-1	20
SLC-B-NANO	0.51" - 0.62" (13.0 - 15.7 mm)	N-Type	0.53" – 0.63" (13.5 – 16.0 mm)	80-6114-9598-9	20

"RoHS 2011/65/EU" means that the product or part does not contain any of the substances in excess of the maximum concentration values ("MCVs") in EU RoHS Directive 2011/65/EU. The MCVs are by weight in homogeneous materials. This information represents 3M's knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

3M is a trademark of 3M Company.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of 12 months from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.



Communication Markets Division

6801 River Place Blvd.
Austin, TX 78726-9000 USA

Phone 1-800-426-8688
Fax 1-800-626-0329
Web 3M.com/Telecom

Please recycle. Printed in USA © 3M 2015.
All rights reserved. 80-6113-9855-5

