




THERMAL IMAGING TEMPERATURE SENSOR

FLIR A35/A65™


The FLIR Ax5-Series of thermal imaging temperature sensors offers comprehensive visual temperature monitoring for process control and quality assurance applications as well as condition monitoring and fire prevention. The A35 and A65 integrate seamlessly into existing systems and are the only thermal imaging temperature sensors on the market to provide temperature linear output through GenICam™ compliant software.



VISUALIZE HEAT

These non-contact temperature sensors are enhanced with thermal imaging

- Detect temperature differences as small as 50 mK
- Choose the right field of view for your measurement area, from wide (90°) to narrow (6.2°)
- Measures accurately in conditions up to 140°F (60°C)



COMMUNICATE DATA SEAMLESSLY

Stream temperature linear output through GenICam™ compliant software

- Integrate easily with Cognex, National Instruments, and other top machine vision systems
- Stream thermal images at up to 60 Hz directly to your system, for instant data analysis
- Synchronize cameras for stereoscopic applications



DESIGNED TO FIT YOUR APPLICATIONS

Get more out of your data with advanced analysis tools

- Compact size makes for easy installation in electrical cabinets and other small spaces.
- Offering the stability of a GigE Vision lockable connector, and the flexibility of Power over Ethernet (PoE)
- Ideal for any environment, the cameras' robust design can withstand harsh conditions



SPECIFICATIONS

Image and Optical Data		A35	A65
IR Resolution		320 x 256	640 x 512
Thermal Sensitivity/NETD		<0.05°C @ 30°C (86°F) / 50 mK	
Image Frequency		60 Hz	30 Hz
Focus		Fixed	
Detector Data			
Detector Type		Uncooled VOx microbolometer	
Spectral Range		7.5 – 13 μm	
Detector Pitch		17 μm	17 μm
Detector Time Constant		12 ms (typical)	
Measurement			
Object Temperature Range		-25°C to 100°C (-13°F to 212°F) -40°C to 550°C (-40°F to 1022°F)	
Accuracy		±5°C (±9°F) or 5% of reading	
Ethernet			
Ethernet Type		Gigabit Ethernet, control and image	
Ethernet Standard, Connector		IEEE 802.3, RJ-45	
Ethernet Communication		GigE Vision ver. 1.2, Client API GenICam compliant	
Ethernet Image Streaming		8-bit monochrome @ 60 Hz	8-bit monochrome @ 30 Hz
		Signal linear/DDE; Automatic/Manual; Flip H&V	
Bit Rate		14-bit 320 x 256 @ 60 Hz	14-bit 640 × 512 pixels @ 30 Hz
		Signal linear/DDE; Temperature linear GigE Vision & GenICam compatible	
Ethernet Power		Power over Ethernet, PoE IEEE 802.3af class 0 power	
Ethernet Protocols		TCP, UDP, ICMP, IGMP, DHCP, GigE Vision	
Digital Input/Output			
Digital Input		1× opto-isolated, "0" <1.2 VDC, "1" = 2–25 VDC	
Digital Output		1× opto-isolated, 2–40 VDC, max. 185 mA	
Digital I/O, Isolation Voltage		500 VRMS	
Digital I/O, Supply Voltage		2 – 40 VDC, max 200 mA	
Digital I/O, Connector Type		12-pole M12 connector (shared with digital synchronization and external power)	
Synchronization In		Frame Synch In to control camera 1x, non-isolated	
Synchronization In Type		LVC Buffer @ 3.3 V, "0" <0.8 V, "1" >2.0 V	
Synchronization Out		Frame Synch Out to control another FLIR Ax5 unit 1x, non-isolated	
Synchronization Out Type		LVC Buffer @ 3.3 V, "0" = 24 MA max, "1" = –24 mA max	
Digital Synchronization Connector Type		2-pole M12 connector (shared with Digital I/O and External power)	
Power System		A35	A65
External Power Operation		12/24 VDC, < 3.5 W nominal < 6.0 W absolute max	
External Power Connector Type		12-pole M12 connector (shared with Digital I/O and Digital Synchronization)	
Voltage		Allowed range 10 – 30 VDC	

Environmental Data	
Operating Temperature Range	–15°C to 60°C (5°F to 140°F)
Storage Temperature Range	–40°C to 70°C (–40°F to 158°F)
Humidity (Operating and Storage)	IEC 60068-2-30/24 h 95% relative humidity 25°C to 40°C (77°F to 104°F)
EMC	EN 61000-6-2 (Immunity), EN 61000-6-3 (Emission), FCC 47 CFR Part 15 Class B (Emission)
Encapsulation/Bump/Vibration	IP 40 (IEC 60529), 25 g (IEC 60068-2-27), 2 g (IEC 60068-2-6), MIL-STD810G

Physical Data	
Camera Size (L x W x H)	7.5, 9, and 13 mm lenses: 104.1 × 49.6 × 46.6 mm (4.1 × 1.9 × 1.8 in)
	25 mm lens: 107.8 × 49.6 × 46.6 mm (4.2 × 1.9 × 1.8 in)
	A35 w/ 50 mm lens: 141.1 × 58.4 × 58.4 mm (5.7 × 2.3 × 2.3 in)
	A65 w/ 50 mm lens: 144.1 × 58.4 × 58.4 mm (5.7 × 2.3 × 2.3 in)
Tripod Mounting	UNC ¼"–20 (three sides)
Base Mounting	4 × M3 thread mounting holes (bottom)
Housing Material	Magnesium and aluminum

Packaging	
Contents	Thermal imaging camera with lens, base support, printed documentation (some models include focus adjustment tool)

Part Number	Camera
73309-0102	FLIR A35 f=9 mm with SC kit
83225-0101	FLIR A35 FOV 13 (60 Hz)
83213-0102	FLIR A35 FOV 25 (60 Hz)
83207-0102	FLIR A35 FOV 45 (60 Hz)
83250-0101	FLIR A35 FOV 6.5 (60 Hz)
83209-0102	FLIR A35 FOV 69 (30 Hz)
73413-0102	FLIR A65 f=13 mm with SC kit (30 Hz)
73513-0102	FLIR A65 f=13 mm with SC kit (7.5 Hz)
75050-0101	FLIR A65 FOV 12.4 (30 Hz)
75025-0101	FLIR A65 FOV 25 (30 Hz)
75013-0101	FLIR A65 FOV 45 (30 Hz)
75010-0101	FLIR A65 FOV 6.2 (30 Hz)
75007-0101	FLIR A65 FOV 90 (30 Hz)