



775 Combination Carbon Monoxide & Combustion Gas Leak Detector

New! Two Tools in One!

The TPI 775 is a state-of-the-art Carbon Monoxide and Combustible Gas Leak Detector. It is the first of its kind to combine both detection technologies into one easy to use hand-held affordable instrument.



The TPI 775 is a state-of-the-art Carbon Monoxide and Combustible Gas Leak Detector. It is the first of its kind to combine both detection technologies into one easy to use hand-held and affordable instrument.

- Easy to use
- One hand operation
- Auto zero
- Back light
- Visible and audible alarm

Turn over for
technical
information
and accessory
part numbers.

**The
Value
Leader™**

Sensor Specifications

| Type | Resolution | Range | Accuracy |
|------|------------|-------------|--------------------------------------|
| Leak | <50ppm | 0-50,000ppm | ±10% |
| CO | 1ppm | 0-2,000ppm | ±5ppm or 5%; whichever is greater |

visit us at www.tpi-thevalueleader.com

1.888.610.7664

 www.calcert.com

sales@calcert.com



TECHNICAL SPECIFICATIONS AND ACCESSORIES

- Digital Multimeters
- Clamp Meters
- Hand-held Oscilloscopes
- Refrigerant & Combustible Gas Leak Detectors
- Temperature Testers
- BNC Coax Cable Connectors
- Test Leads
- Accessories

Test Products International, Inc.
Headquarters:
9615 SW Allen Blvd.
Beaverton, OR 97005
USA
503-520-9197
Fax: 503-520-1225
email:
info@tpi-thevalueleader.com

Test Products International, Ltd.
342 Bronte St. South
Unit 9
Milton, Ontario L9T 5B7
Canada
905-693-8558
Fax: 905-693-0888
email:
info@tpicanada.com

Test Products International UK Ltd.
Longley House, East Park
Crawley, West Sussex
RH10 6AP England
Tel: +44 (0)1293 561212
Fax: +44 (0)1293813465
contactus@tpieurope.com

775 Combustion Carbon Monoxide & Combustion Gas Leak Detector

SPECIFICATIONS

| | |
|-----------------------------------|---|
| Alarms | Visual and Audible |
| Response Time: | |
| CO | 90% in 30 seconds |
| Leak | Instantaneous |
| Goose Neck Length | 16" (406mm) |
| Dimensions | 9.5" x 2.9" x 2.2" (240mm x 74mm x 55mm) |
| Power | 2C Alkaline Batteries |
| Power Consumption | About 400mW in typical use |
| Operating and Storage Temperature | 32° to 120°F (0° to 50°C) |
| Warranty | 3 years |
| Standard Accessories | Soft Carrying Case Manual 2C Alkaline Batteries |
| Optional Accessories | Earphones |

SENSOR SPECIFICATIONS

| Type | Resolution | Range | Accuracy |
|------|------------|-------------|--------------------------------------|
| Leak | <50ppm | 0-50,000ppm | ±10% |
| CO | 1ppm | 0-2,000ppm | ±5ppm or 5%; whichever is greater |

Distributed By:



To learn about the entire
line of TPI products visit:

www.tpi-thevalueleader.com

L 775-1104
Copyright © 2004 Test Products International, Inc.