

HOLE SAWS

Bi-Metal Hole Saws



- Cut through steel, tin, aluminum, fiberglass, wood and plastic
- Deep 1-5/8" (41 3 mm) cutting depth allows for cutting through 2" x 4" wood studs
- Extra-tough bi-metal blade – we use the highest grade of tool steel to outlast competitor's blades That beats premature saw replacement and saves you money
- Steam oxide finish – no paint to gum up and slow cutting - The saw runs cooler for longer life and better performance
- Extra-thick backplate minimizes vibration for smoother, easier, less tiring cutting
- Made in USA with Global Components

CAT. NO.	POP UPC NO.	BULK CAT. NO.	BULK UPC NO.	BULK QTY.	ACTUAL HOLE SIZE		HOLE DIA.		COPPER PIPE SIZE	USE WITH QUICK CHANGE ARBOR NO.	USE WITH STD. ARBOR NO.
					INCH	MM	CONDUIT	ISO			
825-11/16	19133	—	—	—	11/16	17.5		ISO-16	3/8"	02800*	37157, 37155, or 38522
825-3/4	19134	825B-3/4	29828	25	3/4	19.0			1/2"		
825-7/8	19136	825B-7/8	29829	50	7/8	22.2	1/2"		5/8"		
825-1	19138	825B-1	03447	50	1	25.4		ISO-25	3/4"		
825-1-1/8	19141	825B-1-1/8	29831	50	1-1/8	28.6	3/4"		3/4"		
825-1-1/4	19144	825B-1-1/4	03456	24	1-1/4	31.7			1"		
825-1-5/16	19145	—	—	—	1-5/16	33.3		ISO-32			
825-1-3/8	19146	825B-1-3/8	29832	24	1-3/8	35.0	1"				
825-1-7/16	19147	—	—	—	1-7/16	36.5					37156 or 37154
825-1-1/2	19148	—	—	—	1-1/2	38.1			1-1/4"		
825-1-5/8	19150	—	—	—	1-5/8	41.3		ISO-40		02801*	37156
825-1-3/4	19152	825B-1-3/4	29834	24	1-3/4	44.4	1-1/4"		1-1/2"		
825-1-7/8	19154	—	—	—	1-7/8	47.6					
825-2	19155	825B-2	29835	24	2	50.8	1-1/2"	ISO-50			
825-2-1/8	19158	825B-2-1/8	38031	24	2-1/8	54.0					
825-2-1/4	19159	825B-2-1/4	03457	24	2-1/4	57.2			2"		
825-2-3/8	19161	825B-2-3/8	38034	24	2-3/8	60.3			2"		
825-2-1/2	19162	825B-2-1/2	29836	24	2-1/2	63.5	2"	ISO-63	2"		
825-2-5/8	19164	825B-2-5/8	38036	18	2-5/8	66.7					
825-2-3/4	19165	—	—	—	2-3/4	69.8					
825-2-7/8	19166	—	—	—	2-7/8	73.0					
825-3	19167	825B-3	29837	18	3	76.2	2-1/2"		2-1/2"		37156
825-3-1/4	19169	—	—	—	3-1/4	82.5					
825-3-1/2	19171	825B-3-1/2	03458	18	3-1/2	88.9					
825-3-5/8	19172	825B-3-5/8	29838	18	3-5/8	92.1	3"				
825-3-3/4	19174	825B-3-3/4	38045	10	3-3/4	95.2					
825-4	19176	825B-4	03469	10	4	101.6					
825-4-1/8	19177	—	—	—	4-1/8	104.8	3-1/2"		3-1/2"		
825-4-1/4	19178	825B-4-1/4	38049	10	4-1/4	108.0			4"		
825-4-3/8	19179	—	—	—	4-3/8	111.1					
825-4-1/2	19180	825B-4-1/2	38051	10	4-1/2	114.3	4"				
825-4-3/4	19181	—	—	—	4-3/4	120.6					
825-5	19182	825B-5	38053	5	5	127.0				02802*	37156
825-5-1/2	19183	825B-5-1/2	38054	5	5-1/2	139.7			5"		
825-6	19184	825B-6	38055	5	6	152.4					

*See page 119-120 for Quick Change adapter information