Leica NA700 levels

Jobsite tough – simply without compromise







Superior performance and first-class service

The Leica NA700 levels defy the toughest of building-site environments. Come rain or shine, in dazzling light or shade, they provide reliable and extremely precise measurement results. Even the vibration from heavy construction machinery does not affect their accuracy. No need for regular checks in the workshop or constant readjustment - saving time and money!

When it comes to extreme robustness and optimum measuring accuracy, the Leica NA700 levels are hard to beat.

Our protection for your success

Comprehensive expert knowledge and a global understanding of what our customers want and need take top priority at Leica Geosystems. Our close co-operation with professionals from the field results in user-friendly products that are precisely tailored to customer expectations. Our products are highly reliable, accurate and robust - even under the toughest of building-site conditions. They boost the productivity and the success of our customers. With PROTECT by Leica Geosystems, we offer a first-class service that you can rely on any time, anywhere.



PROTECT is subject to the Leica Geosystems International Limited Warranty and the General Terms and Conditions for PROTECT, which you can find at: www.leicageosystems.com/protect.

*Available through free online registration within 8 weeks of purchase.



Simply without compromise

Thanks to the constant application of the latest technology combined with the highest quality requirements during production, Leica NA700 levels enjoy an outstanding reputation across the globe.



Simple operation

The prism makes it extremely easy to adjust the horizontal level.



No conversion

The read-out is right next to the target telescope, in degrees or in gon as required.



Convenient pointing

The target dioptre adjustment makes it quick and easy to focus on the levelling image prevent eyes from quickly tiring. staff.




Comfortable read-out

The ergonomic look and sharp, upright



Constant clear view

The nitrogen-filled telescope prevents the lens from fogging up and ensures a clear view.



Outstanding contrast

The high luminosity guarantees reading accuracy, even in unfavourable lighting.



Impact-resistant

Even when faced with vibrations and impacts, the Leica NA700 levels continue to work reliably and with precision.



Water-tight and dust-tight

Water, dust and dirt will not stop the Leica NA700 levels.

Technical data

·	Leica NA720	Leica NA724	Leica NA728	Leica NA730	Leica NA730 plus
Magnification	20×	24×	28×	30×	30×
Telescope image	Upright				
Nitrogen-filled telescope	Yes				
Lens diameter	30 mm	36 mm	40 mm	40 mm	40 mm
Shortest target distance	0.5 m	0.5 m	0.5 m	0.7 m	0.7 m
Angle measurement	Choose between 360 degrees / 400 gon				
Distance measurement					
- Multiplication factor	100				
- Additive constant	0				
Circular level	10' / 2 mm				
Horizontal drive	Both sides, endless				
Accuracy (standard deviation)					
per km double levelling	2.5 mm	2 mm	1.5 mm	1.2 mm	0.7 mm
Single measurement with 30 m target	1.5 mm	1.2 mm	1 mm	0.8 mm	0.4 mm
distance					
Compensator					
Setting accuracy	<0.5"	<0.5"	<0.3"	<0.3"	<0.3"
Tilt area	± 15'				
Environmental stresses					
Drop resistance	ISO 9022-33-5				
Water-tightness and dust-tightness	IP 57 (submersible)				
Temperature range					
- Operating temperature	−20 to +50°C				
- Storage temperature	−40 to +70°C				
Dimensions					
Size	19×12×12 cm	19×12×12 cm	21×12×12 cm	21×12×12 cm	21×12×12 cm
Weight	1.6 kg	1.6 kg	1.7 kg	1.7 kg	1.7 kg

Tripod and levelling staffs

Optimise the performance of your Leica NA700 level with the specially tailored accessories.



CTP104 round-base tripod

Aluminium tripod with carrying straps, fast clamps, 5/8" screw. Telescopic from 85–160 cm Item no. 767710

CLR 101 telescopic levelling staff

Length: 4m, 4-piece, E pattern on front, mm indexing on reverse Item no. 727587

CLR 102 telescopic levelling staff


Length: 5 m, 4-piece, E pattern on front, mm indexing on reverse Item no. 727588

CLR 104 telescopic levelling staff

Length: 5 m, 5-piece, E pattern on front, mm indexing on reverse Item no. 743 420







Tools for Pro by Leica Geosystems Overcome the challenges of the building site

- **PROTECT by Leica Geosystems** Benefit from fast access to the first-class range of PROTECT services and register your new Leica NA700 level for an additional "year without extra costs" using your smartphone or tablet
- Sales and service network Quickly find the sales and service contact for Leica Geosystems in your area
- Product catalogue At the push of a button, select the right product for your building-site application
- News Don't miss any of the innovations or latest technologies from Leica Geosystems!
- Leica DISTO™ sketch Optimise your workflow with quick measurements and professional documentation





Tools for Pro



Figure, description and technical data are non-binding; subject to changes.

712696en - 03.15 - galledia







