

Unique Surface Probes



All the probes in this series meet the Standard Limits of Error.

Model No. 88106(*)

Right-angle probe for fast response times. Sheath length is 102 mm (4"). Max surface temperature is 760°C (1400°F).

Replacement elements not included, to purchase additional elements order Model No. 88106()-RE*

Model No. 88107(*)

Right-angle, long reach probe with fast response design. Sheath length is 203 mm (8"), with 760°C (1400°F) max surface temperature.

Replacement elements not included, to purchase additional elements order Model No. 88107()-RE*

All models shown smaller than actual size.

Model No. 88108(*)


Right-angle, long 300 mm (12") reach probe with fast response design. 760°C (1400°F) max surface temperature.

Replacement elements not included, to purchase additional elements order Model No. 88108()-RE*

Model No. 88010(*)

Long, 300 mm (12") reach version of the 88006. Fast response design with 760°C (1400°F) max surface temperature for use in oven and furnaces.

Replacement elements not included, to purchase additional elements order Model No. 88010()-RE*



TAS adaptor

All models supplied with a molded SMP or SMPW subminiature male connector. TAS adaptor is sold separately.

For a male straight M8 plug add "M8-S-M" to the model number, for a male straight M12 plug add "M12-S-M" to the model number.
For a male right-angled M8 plug add "M8-R-M" to the model number, for a male right-angled M12 plug add "M12-S-M" to the model number.



For Temperatures up to 760° C (1400°F)

* Specify Calibration:

K: CHROMEPA™-ALOMEGA™

E: CHROMEPA™-Constantan

Visit us online for dimensions.

Ordering Example:

88018K, Type K surface probe.

Model No. 88007(*)

Miniature, fast response probe. Ideal for measuring the surface temperature of small electronic parts. 250°C (480°F) max surface temperature.

*Replacement elements not included, to purchase additional elements order
Model No. 88007(*)-RE*

Model No. 88006(*)

Miniature, fast response probe with 480°C (900°F) max surface temperature. Ideal for surface temperatures of small electronic parts.

*Replacement elements not included, to purchase additional elements order
Model No. 88006(*)-RE*


All models shown smaller than actual size.

Model No. 88016(*)

Visit us online for dimensions.

High temperature, right-angle probe, with miniature pencil type head. Best suited to stationary surfaces, with sensing head parallel to the handle. 480°C (900°F) max surface temperature.

*Replacement elements not included, to purchase additional elements order
Model No. 88016(*)-RE*



TAS adaptor
All models supplied with a molded SMP or SMPW subminiature male connector. TAS adaptor is sold separately.



Miniature connector.



Model No. 88026(*) High temperature, right-angle probe, with miniature pencil type head. Best suited to stationary surfaces, with sensing head perpendicular to the handle. 480°C (900°F) max surface temperature.

*Replacement elements not included, to purchase additional elements order
Model No. 88026(*)-RE*


** Specify calibration: K - Type K Thermocouple E - Type E Thermocouple
Ordering Example: 88007K probe with type K Thermocouple.*

Replaceable Element Design

Factory Replaceable Element: OMEGA™ can install replaceable elements and check the probe for an additional cost.


*To order Replaceable Elements, add suffix "-RE" to model number.
Ordering Example: 88026K-RE for 88026K probe.*

** Insert calibration needed, e.g. K (Type K thermocouple).*




Model No. 88007K and replaceable element, Model No. 88007K-RE.


Unique Surface Probes Series 88000




88001




88002 88003




88006




88007




88008




88010




88011




88012




88016




88026




88101




88102




88103




88104



88105




88106




88107

Dimensions: mm (in)


Unique Surface Probes Series 88000/98000




88108




98201 Swivel
88201




98202 Swivel
88202




98203 Swivel
88203




98220 Swivel
88220




98221 Swivel
88221




88222




88223




88224




98225 Swivel
88225




98226 Swivel
88226




98227 Swivel
88227




88301




88305



88306




88307




88308

Dimensions: mm (in)

Model 88009



Model 88014



Model 88013

