





PART# 91000-A Deluxe A/C Clutch Hub Puller & Installer

REMOVING PROCEDURE:

- 1. Remove shaft nut or retaining ring.
- 2. Thread removing tool onto hub. Position center screw against the end of compressor shaft.
- 3. Hold body of remover with wrench and turn center screw into remover body to remove clutch hub assembly.

INSTALLING PROCEDURE:

- 1. Ensure frictional surface of clutch plate and rotor is clean.
- 2. Align shaft key with shaft keyway and place clutch plate and hub assembly on compressor shaft. (Do not drive or pound on clutch hub or shaft, as this may cause internal damage to compressor.)
- 3. Attach installing tool onto compressor shaft. (Body of installing tool should be backed off sufficiently to allow center screw to be threaded fully onto end of compressor shaft).
- 4. Hold center screw with wrench and tighten hex portion of installer to press hub onto shaft.
- 5. Tighten body several turns until the air gap between the friction surfaces is .020 - .030 inch.
- 6. Remove installer and check for proper positioning of shaft key.
- 7. Install shaft nut or retaining ring. (Refer to manufacturer specification for correct torque).
- 8. Spin pulley by hand to check for free operation.



- · Puller parts can break under stress!
- Wear safety goggles (user and bystanders)! Read and follow instructions.
- Do not heat pullers! • Do not over stress pullers!
- · Be aware of hand positions.
 - · Broken parts can cause injury!

 - · Avoid contact with refrigerant!

Compressor Type Used Vehicles from (1989 - present)								
Make	Nippon	Sanden	York Tecumseh	Harrison	Zexel Hitachi	Seiko Seiki	Diesel Kiki	
Acura	x							
American Motors		х						
Audi	х		Х					
BMW		х	Х					
Buick				Х				
Cadillac				Х				
Chevrolet				Х				
Chevrolet Truck				х				
Chrysler	х							
Dodge	х							
Dodge Truck	х	х						
Eagle	х	х						
Fiat		х						
Ford	х	х						
Ford Truck	Х	Х						
GMC Truck				Х				
Honda	Х							
Hyundai		х						
Infinity					Х			
Isuzu				х				
Jaguar		Х	Х	Х				
Jeep		Х	Х					
Lexus	Х							
Lincoln	Х							
Mazda	х							
Mercedes Benz			Χ	Х				
Mercury	Х							
Mitsubishi	Х							
Nissan					Х			
Oldsmobile				Х				
Peugeot		х						
Plymouth	х							
Plymouth Truck	х							
Pontiac				Х				
Porsche		х	Х					
Renault		Х						
Saab						Х		
Saturn					Х			
Subaru		Х	Х					
Suzuki	Х							
Toyota	х							
Volkswagon	Х	Х	Х					
Volvo							Х	

Make	F	Remover	Installer		
Harrison GM					
DA-6, HR-6 & V5	91212	Nut & Arbor	90458 91260	Nut, Bearing & Arbor	
A-6 & Earlier R4	90454	Nut & Arbor	90458	Nut, Bearing & Arbor	
R4	90454 91195		90458 91260	Nut, Bearing & Arbor	
Nippondenso			1		
Ford / Chrysler					
A590, C171 & FS-6	91122	Nut &	90458	Nut &	
	91212	Arbor	1052-001	Arbor & Washer	
For FS-6 W / Special	91122	Nut & Arbor	90458	Nut &	
24mm x 2.0	[1052-001	Arbor & Washer	
New Style	90454	Nut & Arbor	90458	Nut &	
			1052-001	Arbor & Washer	
<u>Sanden</u>	90902	Puller Plate & Arbor			
York / Tecumseh	91122	Nut &	90458	Nut &	
HR980	91212	Arbor	1052-001	Arbor & Washer	
Zexel / Mitsubishi	92260	Arbor &	T		
CH Series	90902	Puller Plate			

