



**FIBER TOOLS**

FAST, ACCURATE AND RELIABLE FIBER CLEAVING

# 915CL OPTICAL FIBER CLEAVER

SPLICE AND CLEAVE FIBER THE RIGHT WAY!

## FAST

Cleaved Fiber remains in the adapter ready to splice and is compatible with the 915FS, FSP200 or the 910FS fusion splicers.

## ACCURATE

Precision-engineered blades accurately cleave fibers for minimal loss.

## RELIABLE

Field tested to perform the dust bin safely collects end cuts.



1.888.610.7664



[www.calcert.com](http://www.calcert.com)

[sales@calcert.com](mailto:sales@calcert.com)

# 915CL

## OPTICAL FIBER CLEAVER

### BENEFITS

- Accurate Cleave. Cleave multi-mode and single-mode fiber optic cables.
- Long Life. Blades rotate for longer life - over 48,000 cleaves.
- Adaptable. Supports 250um, 900um fibers and loose tube fibers.
- Fast. For use with the 915FS, FSP200 or the 910FS Optical Fusion Splicer for maximum speed and efficiency with auto return mechanism.
- Dust bin. Safely collects end cuts during cleaving process.
- Fixed Clamp. Allows the technician to use the 915CL as a standalone cleaver.

### SPECIFICATIONS:

APPLICABLE FIBERS:	SM (G.652); MM (G.651); DS (G.653); NZDS (G.655); BIF (G.657)
FIBER CLEAVED LENGTH	5mm - 20mm
CLADDING DIAMETER:	125µm
COATING DIAMETER:	0.25 mm and 0.9 mm
FIBER COUNT:	Single
CLEAVING ANGLE:	< 1.5°
BLADE LIFE	48,000 Cleaves
WEIGHT	0.56 lbs (255 g)
DIMENSIONS (HXWXD)	2.29 x 2.17 x 1.89" (58 x 55 x 48 mm)

### ORDERING INFORMATION:

CAT. NO.	DESCRIPTION
915CL	915CL Optical Fiber Cleaver
915CL-Blade	Cleaving Wheel (915CL)
01332	250µm Adapter (Pair)
01333	900µm Adapter (Pair)
05801	Loose Tube Adapter (Pair)
03245	3mm Adapter (Pair)
PA1171	ProGrip 5-in-1 Fiber Optic Stripper



915FS

FOR USE WITH THE 915FS, FSP200 OR  
910FS FUSION SPLICERS

CAT. NO.	DESCRIPTION
PA1177	ProGrip 3-in-1 Fiber Optic Stripper
10997	Economy Fiber Optic Stripper
PA1511	Kevlar Cutter
MSS100	Mid Span Slitter
915CL-CLAMP	Fixed Clamp for 915CL with Screw
04268	Replacement Screw for Fixed Clamp

The 915CL is supplied with a fixed clamp and a mounting screw that the technician can use to permanently mount the fixed clamp to the cleaver. Shipped not assembled.

TC6580 03/23



*Renewed Vision. Innovation Forward.*