FLIR Axxx-SERIES SMART SENSOR

Fixed-Mount Thermal Camera



Key Features:

- On-camera temperature measurement and alarming tools provide immediate results
- Unrivaled connectivity and on-the-edge computing for easy integration into web applications
- Robust and reliable thermal imaging for applications where temperature accuracy matters

Main Applications:

- Continuous thermal monitoring of critical infrastructure
- Early fire detection for fast response
- Temperature-based machine and process control

SPECIFICATIONS

Detector Data	Standard Configuration	Advanced Configuration
IR resolution	320 × 240 (A400), 464 × 348 (A500), or 640 × 480 (A700)	
Visual resolution	1280 × 960	
Focal plane array/spectral range	<30 mK to <50 mK, lens dependent	
Lenses	°, 14°, 24°, 42°, 80°, FlexView® Dual FOV (24°/14°), FlexView® Dual FOV (42°/24°) lenses	
IR camera focus	One-shot contrast, motorized, manual	
Measurement		
Object temperatures	-20°C to 120°C (-4°F to 248°F) 0°C to 650°C (32°F to 1202°F) A400/A500: 300°C to 1500°C (572°F to 2732°F) A700: 300°C to 2000°C (572°F to 3632°F)	
Accuracy	±2°C (±3.6°F) or ±2% of reading	
Measurement analysis		
Standard functions	10 spotmeters, 10 boxes, 3 Deltas, 1 isotherm, 1 iso-coverage, 1 reference temperature	10 spotmeters, 10 boxes & mask polygons, 3 Deltas, 2 isotherm, 2 iso-coverage, 1 reference temperature, 2 lines, 1 polyline
Automatic hot/cold detection	Max./min. temperature value and position shown within box	
Scheduled response	SFTP (image), SMTP (image and/or measurement data/result)	
Measurement frequency	Up to 10 Hz	
Measurement result read-out	Yes; common protocols include EtherNet/IP, Modbus TCP, MQTT, and REST API	
Dynamic Range	16-bit	

Alarm	Standard Configuration	Advanced Configuration
Alarm function	On any selected measurement function; digital in; internal camera temperature	
Alarm output	Yes: common output includes e-mail, EtherNet/IP, Modbus TCP, RESTful API, and ONVIF (advanced only)	
Video streaming, RTSP protocol		
Unicast	Yes	
Multicast	Yes	
Multiple image streams	Yes	
RTSP protocol - video stream 0		
Source	Visual, IR, MSX®	
Contrast enhancement	FSX®, histogram equalization (IR only)	
Overlay	With, without	
Pixel format	YUV411	
Encoding	H.264/MPEG4/MJPEG	
RTSP protocol - video stream 1		
Source	Visual	
Overlay	No	
Pixel format	YUV411	
Encoding	H.264/MPEG4/MJPEG	
Radiometric streaming		
Source	-	IR
Pixel format	-	MONO 16
Encoding	-	Compressed JPEG-LS; FLIR radiometric

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact. ©2024 Teledyne FLIR, LLC. All rights reserved.

Revised 09/25/24
RH24-0539-INS

1.888.610.7664 www.calcert.com sales@calcert.com

FLIR Axxx-SERIES SMART SENSOR

Fixed-Mount Thermal Camera

SPECIFICATIONS, CONT.

Ethernet	Standard Configuration	Advanced Configuration
Interface	Wired; Wi-Fi*	
Connector types	M12 8-pin X-coded, female; RP-SMA, female	
Ethernet type & standard	1000 Mbps, IEEE 802.3	
Ethernet power	Power over Ethernet, PoE IEEE 802.3af class 3	
Ethernet protocols	Include EtherNet/IP, Modbus TCP, and MQTT	
Digital input/output		
Connector type	M12 Male 12-pin A-coded (shared with ext. power)	
Digital input	2× opto-isolated, Vin (low) = 0-1.5 V, Vin (high) = 3-25 V	
Digital output	3× opto-isolated, 0–48 V DC, max. 350 mA (derated to 200 mA at 60°C). Solid-state opto relay, 1× dedicated as fault output (NC)	
Power system		
Connector type	M12 Male 12-pin A-coded (shared with Digital I/O)	
Power consumption	7.5 W at 24 V DC typical; 7.8 W at 48 V DC typical; 8.1 W at 48 V PoE typical	
Wi-Fi*		
Connector type	Female RP-SMA	

*Optional feature

The FLIR A-Series cameras are designed for configuration to your specific needs. Specifications are subject to change without notice.

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact. ©2024 Teledyne FLIR, LLC. All rights reserved.

Revised 09/25/24
RH24-0539-INS

1.888.610.7664 www.calcert.com sales@calcert.com