

F34-HE Refrigerated - Heating Circulator

The HighTech Series features refrigerated heating /circulators with innovative technology for sophisticated applications. The instruments provide powerful, electronically adjustable pressure and suction pumps.

The instruments can be used for internal as well as external temperature control applications of closed and open systems.

Your advantages

- VFD COMFORT DISPLAY
- Keypad for setpoints, warning/safety values and menu functions
- ICC (Intelligent Cascade Control), self-optimizing temperature control
- ATC3 3-Point-Calibration
- Pt100 External sensor connection for measurement and control
- SMART PUMP, electronically adjustable pump stages
- Adjustable pressure and suction pump
- Adjustable high temperature cut-out, visible via display
- RS232 interface for online communication
- Optional: analogue interfaces
- Integrated programmer for 10 program steps
- Active Cooling Control



Technical data

Available voltage versions		Bath	
Order No.	9 212 634	Bath cover	integrated
Available voltage versions:		Usable bath opening cm (W x L / D)	24 x 30 / 15
9 212 634.02	115V/60Hz (Nema N5-15 Plug)		
9 212 634.03	230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)		
9 212 634.05	230V/50Hz (CH Plug Type SEV 1011)		
9 212 634.04	230V/50Hz (UK Plug Type BS1363A)		
9 212 634.13	230V/60Hz (Schuko Plug - CEE 7/4 Plug Type F)		
Cooling		Other	
Cooling of compressor	1-stage Air	Sound pressure level dbA	54
		Classification	Classification III (FL)
		IP Code	IP 21
		Pump type	Immersion Pump
Electronics		Dimensions and volumes	
Digital interface	Profibus optional	Weight kg	44
External pt100 sensor connection	integrated	Barbed fittings inner diameter	8/12 mm
Integrated programmer	1x10 steps	Dimensions cm (W x L x H)	38 x 58 x 64
Temperature control	ICC	Filling volume l	14 ... 20
Absolute temperature calibration	3 Point Calibration	Pump connections	M16x1 male
Temperature display	VFD		
Temperature setting	Keypad		
Temperature values			

Setting the resolution of the temperature display °C	0.01
Working temperature range °C	-30 ... +150
Temperature stability °C	±0.01
Temperature stability external °C	±0.01 ... ±0.2
Ambient temperature °C	+5.0 ... +40.0
Temperature display resolution °C	0.01

Performance values

115V/60Hz (Nema N5-15 Plug)

115V/60Hz				
Heating capacity kW		1		
Cooling capacity (Ethanol)				
°C	20	0	-20	-30
kW	0.45	0.32	0.14	0.03
Viscosity max. cST		70		
Refrigerant		R134a		
Filling volume g		120		
Global Warming Potential for R134a		1430		
Carbon dioxide equivalent t		0.172		
Pump capacity flow rate l/min		22 ... 26		
Pump capacity flow pressure bar		0.4 ... 0.7		
Maximum suction bar		0.2 ... 0.4		

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)

230V/50Hz				
Heating capacity kW		2		
Cooling capacity (Ethanol)				
°C	20	0	-20	-30
kW	0.45	0.32	0.14	0.03
Viscosity max. cST		70		
Refrigerant		R134a		
Filling volume g		120		
Global Warming Potential for R134a		1430		
Carbon dioxide equivalent t		0.172		
Pump capacity flow rate l/min		22 ... 26		
Pump capacity flow pressure bar		0.4 ... 0.7		
Maximum suction bar		0.2 ... 0.4		

230V/50Hz (CH Plug Type SEV 1011)

230V/50Hz	
Heating capacity kW	2

Cooling capacity (Ethanol)

°C	20	0	-20	-30
kW	0.45	0.32	0.14	0.03

Viscosity max. cST	70
Refrigerant	R134a
Filling volume g	120
Global Warming Potential for R134a	1430
Carbon dioxide equivalent t	0.172
Pump capacity flow rate l/min	22 ... 26
Pump capacity flow pressure bar	0.4 ... 0.7
Maximum suction bar	0.2 ... 0.4

230V/50Hz (UK Plug Type BS1363A)

230V/50Hz

Heating capacity kW	2
---------------------	---

Cooling capacity (Ethanol)

°C	20	0	-20	-30
kW	0.45	0.32	0.14	0.03

Viscosity max. cST	70
Refrigerant	R134a
Filling volume g	120
Global Warming Potential for R134a	1430
Carbon dioxide equivalent t	0.172
Pump capacity flow rate l/min	22 ... 26
Pump capacity flow pressure bar	0.4 ... 0.7
Maximum suction bar	0.2 ... 0.4

230V/60Hz (Schuko Plug - CEE 7/4 Plug Type F)

230V/60Hz

Heating capacity kW	2
---------------------	---

Cooling capacity (Ethanol)

°C	20	0	-20	-30
kW	0.45	0.32	0.14	0.03

Viscosity max. cST	70
Refrigerant	R134a
Filling volume g	120
Global Warming Potential for R134a	1430
Carbon dioxide equivalent t	0.172
Pump capacity flow rate l/min	22 ... 26
Pump capacity flow pressure bar	0.4 ... 0.7
Maximum suction bar	0.2 ... 0.4

All Benefits



JULABO. Quality.
Highest standards of quality for a long product life.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Services 24/7.



Early warning system for high/low temperature limits
Maximum safety for applications, optical and audible alarm, convertible to automated cut-off function



Clever pump system
Reliable and consistent pump capacity, electronically adjustable pump stages



Control from the external application
External Pt100 sensor connection for precise measurement and control directly in the external application



For flammable bath fluid
Classification III (FL) according to DIN 12876-1



ATC3. Calibration.
'Absolute Temperature Calibration' for compensating a physically caused temperature difference, 3-point calibration.



Process. Under control.
Full regulation of the dynamics control, access to all important control parameters for individual process optimization.



100 % Cooling capacity
'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



Energy saving cooling
Proportional cooling control for automatic adjustment of cooling power or temporary switch-off of compressor as needed to save up to 90 % energy in comparison to unregulated cooling machines