

Traceable® Dual Thermometer

Dual-probe thermometer gives accurate readings of two separate areas in refrigerators/freezers



Three and a half-foot micro-cable permits refrigerator doors to close on it

- Two-part display shows °F or °C probe temperatures in distinct sections of refrigerator or freezer
- Easy-operate, always-ready unit quickly recalls exact date and time when MIN/MAX temperatures occur
- Audible and visual alarm feature provides alert when temperature rises above or falls below two set points, alarm is programmable in 1 degree increments



Features:

- MIN/MAX memory
- °F/°C switchable
- LCD $\frac{3}{8}$ " high
- Individually serialized, calibrated, and certified Traceable® to NIST

Probe features:

- Bottle (patented): insulates sensor from rapid temperature changes if refrigerator door is opened (1" dia. x 2½")
- Bullet™: water-proof, place anywhere on micro-thin cable (0.187" dia. x ¾" long)

Traceable to NIST for accuracy

Multi-point calibration on an individually-numbered Traceable® Certificate which assures accuracy from our ISO/IEC 17025:2005 (1750.01) calibration laboratory accredited by A2LA. It indicates traceability of measurements to the SI units through NIST or other recognized national measurement institutes (NMI) that are signatories to the CIPM Mutual Recognition Agreement..

Cat. No.	Range	Resolution	Accuracy	Included Probes
4306	-50 to 70°C (-58 to 158°F)	0.1°	±1.0°C	2 Bottles (patented)
4307	-50 to 70°C (-58 to 158°F)	0.1°	±1.0°C	2 Bullets™

Product Specifications

- ▶ **Range:** -58 to 158°F (-50 to 70°C)
- ▶ **Resolution:** 0.1°
- ▶ **Accuracy:** ±1.0°C
- ▶ **4306**
 - Probe:** 2 Bottles (patented)
- ▶ **4307**
 - Probe:** 2 Bullets™
- ▶ **Cable**
 - Length:** 3.5' long
- ▶ **Weight:** 3 ⅔ ounces
- ▶ **Supplied:** battery, flip-open stand, probes, 3½ ft cable, Traceable Certificate

**TRACEABLE®
PRODUCTS**

1.888.610.7664



www.calcert.com

sales@calcert.com