## Traceable® Memory Monitoring Thermometer





View MIN/MAX readings and set alarms to monitor temperature sensitive materials over any time period

- Triple display simultaneously shows MIN/MAX and current temperatures
- Monitors high and low readings overnight, on weekends, or for any time period a significant advantage over current read-only temperatures
- Alarm is programmable in 1° increments and alerts user when temperature rises above or falls below a set point

### **Features:**

- Refrigerator/freezer door closes and seals tightly around micro-thin cable
- Accurately monitor temperatures in freezers, heating blocks, incubators, and refrigerators with an enclosed patented temperature-buffered sensor
- Probe is <sup>5</sup>/<sub>16</sub> inch diameter x <sup>3</sup>/<sub>4</sub>-inch long
- °C/°F switchable

#### Traceable to NIST for accuracy

An individually-numbered Traceable® Certificate is provided which assures accuracy from an ISO/IEC 17025:2005 (1750.01) calibration laboratory accredited by A2LA. It indicates traceability to standards provided by NIST (National Institute of Standards and Technology).

Cat. No. 4048 Traceable® Refrigerator/Freezer Thermometer

# COMPANY

### NPANY 54 •

## Product Specifications

► Range:

–58 to 158°F (–50 to 70°C)

► Resolution: 1°

► Accuracy: ±1°C

► Size: 2<sup>3</sup>/<sub>4</sub> x 4<sup>1</sup>/<sub>4</sub> x <sup>3</sup>/<sub>4</sub>"

► Weight: 4 ounces

► Supplied: batteries, flip-open stand, wall mounting,

Velcro®, Bullet™ probe, magnetic strips, and Traceable® Certificate

www.calcert.com