

3M™ Benchtop Air Ionizer 963E

The use of ionized air in electronics work environments eliminates the build up of potentially damaging static charges. Air ionizers are primarily used to control static charge on nonconductive materials. Grounding is normally used to control charge on conductive objects and personnel, however, nonconductors cannot be grounded to drain electrostatic charge. Ionization is the only method of neutralizing a static charge on a nonconductor. Ionized air can neutralize static charges on circuit board substrates, insulating tapes and plastic objects found in the work area. The 3M Benchtop Air Ionizer 963E blankets the benchtop with ionized air to help prevent static from damaging sensitive electronics.

The 963E ionizer uses AC 100V to 230V power. The ionizer features a two-speed fan, a power indicator lamp, a static-dissipative plastic housing, and a combination metal-plastic stand that can also double as a mounting bracket.

Rapid neutralization of electrostatic charge

The ion-generation technology present in the 963E ionizer is capable of producing extremely large amounts of ions, resulting in nearly instantaneous static charge neutralization. The 963E ionizer is capable of reducing a static charge of 1000V to 100V in less than one second, at a one foot distance, when tested* at the high fan speed. In addition, the powerful fan allows the generated ions to be carried at high speed for long distances. At a distance of three feet, the discharge time only increases to approximately five seconds.

**When tested according to ANSI/ESD S3.1-1991*

Intrinsically balanced, maintenance-free

3M ionizers have a proprietary, intrinsically balanced ion generation system which ensures that equal levels of positive and negative ions are produced despite variations in line voltage, fan speed, and emitter point condition. No adjustment or calibration is required to maintain ion balance. This allows the unit to generate a balanced mix of positive and negative ions - even if the emitter points become dirty.

The 963E ionizer is virtually maintenance free. The ionizer's unique design requires only periodic cleaning of emitter points to maintain optimum performance. The points do not require replacement and the unit does not require adjustment before or after cleaning.



3M™ Benchtop Air Ionizer 963E

Basic Features

- Two versions available, depending on power cord plug
- Neutralizes static charges on nonconductive objects
- Maintains equal balance of positive-negative ions
- Two-speed fan
- Static-dissipative housing
- UL, C-UL, CE, NOM certification



Specifications

Operating Voltage and Frequency	AC 220V/230V 50/60 Hz 0. 12A 20W
Power Outlet	IEC 320 Socket
Supplied Power Cord	6' (1.8 m) cord with IEC 320 and Continental Europe (EURO) plugs or US plug
Dimensions	6.0" W x 7.4" H x 3.0" D (15.2 cm W x 18.8 cm H x 7.8 cm D)
Weight	2.5 lb. (1.1 kg)
Air Velocity	low speed - 100 fpm (0.5 m/s) high speed - 300 fpm (1.5 m/s)
Static Discharge Time*	1' (30 cm) < 1 second at high fan speed 3' (91 cm) < 5 second at high fan speed
Certifications and Approvals	CE, UL, C-UL, NOM
Warranty	1-year

(All values are typical, not specifications)

*When tested according to ANSI/ESD S3.1-1991

