
# Traceable® Refrigerator/Freezer Ultra™ Thermometers





- Smart-Alarm<sup>™</sup> features visual and audible indicators which signal continuously, even if conditions return to non-alarm range
- Triple display simultaneously shows MIN/MAX, and Current temperature readings
- Alarm is programmable in 0.1° increments and alerts user when temperature rises above or falls below a set point

### **Features:**

- Unit is available with 7 different probe configurations
- Ultra<sup>™</sup> accuracy of ±0.5°C between -30 to 50°C, otherwise ±1°C
- Individually serialized, calibrated, and certified Traceable® to NIST

Cat. No.	Probe
4730	1 bottle (patented)
4731	2 bottles (patented)
4732	1 Bullet™
4733	2 Bullets™
4734	1 bottle & 1 Bullet™
4735	1 vaccine bottle (5ml)
4736	2 vaccine bottles (5ml)

### **Probe features:**

- O Bottle (patented): insulates sensor from rapid temperature changes if refrigerator door is opened (1" dia. x 21/2")
- Bullet™: water-proof, place anywhere on micro-thin cable (0.187" dia. x 3/4" long)
- Vaccine bottle (5ml): designed to mimic vaccine bottles and fits in tray (0.6" dia. x 2" long)

### Traceable to NIST for accuracy

An individually-numbered Traceable® Certificate is provided which assures accuracy from an ISO/IEC 17025:2005 (1750.01) calibration laboratory accredited by A2LA. It indicates traceability to standards provided by NIST (National Institute of Standards and Technology).

## **Product Specifications**

–50.0 to 70.0°C ► Range:

Bullet™ Probe

(-58.0 to 158.0°F)

Vaccine Probe

► Accuracy: ±0.5°C between

> –30 to 50°C. otherwise ±1°C

► Resolution: 0.1°

► Cable: 10 feet

▶ Dimensions: 2¾ x 4¼ x ¾ inches

▶ Weight: 4 ounces

Traceable® Certificate, ► Supplied:

> flip-open stand, wall mounting, Velcro®, and magnetic strips



1.888.610.7664

