

Fittings – Filters



MODELS

- A-170**, Stainless Steel Pigtail Siphon.
- A-323**, Elbow Compression Fitting, brass 1/8" NPT to 1/4" metal tubing.
- A-324**, Compression Fitting, brass 1/8" NPT to 1/4" metal tubing.
- A-326**, Compression Fitting, brass 1/8" NPT to 3/8" tubing.
- A-327**, 5/16" Nylon Tube Union.
- A-328**, 1/4" Nylon Tube Union.
- A-329**, 1/8" NPT Close Coupled Street Ell, Brass.
- A-330**, 1/8" Pipe Plug, socket hex, plated steel.
- A-331**, 1/8" NPT Filter Vent Plug, nylon and sintered metal.
- A-332**, Bushing, brass, 1/8" to 1/4" NPT.
- A-333**, Bushing, brass, 1/8" to 1/2" NPT.
- A-334**, Close Nipple, brass, 1/8" NPT.
- A-336**, 90° Street L, brass, 1/8" NPT.
- A-337**, Coupling, brass, 1/8" NPT.
- A-338**, Servel Adapter, brass 3/8" and 5/16" N.F. Threads for gas appliances to 1/8" and 3/16" I.D. rubber or plastic tubing.
- A-339**, Adapter, brass, 1/8" NPT to 3/16" rubber and 1/8" I.D. plastic tubing.
- A-340**, Adapter, nylon, 1/8" NPT to 3/16" I.D. rubber or 1/4" plastic tubing.
- A-342**, "T" Assembly, plastic, for 3/16" I.D. rubber or 1/4" plastic tubing.
- A-343**, "T" Assembly, plastic, for 3/16" plastic tubing.
- A-343-1**, "T" Assembly, plastic, for 1/8" I.D. plastic tubing.
- A-344**, Terminal Tube, Brass 1/4" diameter tube, 8" length (not shown).
- A-345**, Flange, aluminum with gasket and sheet metal screws, 1/8" NPT.
- A-346**, "T" Compression Fitting, brass, 1/4" metal tubing.
- A-349**, Reducer, brass, 1/4" female NPT to 1/8" male NPT.
- A-385**, 1/2" Plastic Hole Plugs 20/bag.
- A-386**, 5/16" Metal Hole Plugs 20/bag.
- A-391**, Line Filter for Capsuhelic® gage, 1/4" female NPT X 1/4" male NPT.
- A-392**, Line Filter for Magnehelic® gage, 1/8" female NPT x 1/8" male NPT.
- A-398**, Probe Extension Adapter for series 640 air velocity transmitter. Brass, 1/2" female NPT x 5/16" compression.
- F222**, Liquid/Particle Filter for compressed air. Removes dirt, water and oil. 22 scfm maximum flow, 1/4" female NPT inlet and outlet.
- 1201-2**, Replacement Filter Element for F222 filter, package of 3.
- F451**, Liquid/Particle Filter for compressed air. Removes dirt, water and oil. 45 scfm maximum flow, 1/4" female NPT inlet and outlet.
- 1201-3**, Replacement Filter Element for F451 filter, package of 3.

Miscellaneous



MODELS

- A-298**, Flat Aluminum Bracket for flush mounting Capsuhelic® gage, 603A, 605, and 3000MR.
- A-299**, Mounting Bracket, flush mount Magnehelic® gage in bracket. Bracket is then surface mounted. Steel with gray hammertone epoxy finish.
- A-300**, Flat Aluminum Bracket for flush mounting Magnehelic® gage.
- A-351**, Pinch Clamp to seal rubber tubing, so in a leakage test.