



**ABM-HOOD &
ABM-HOOD-200**
Owner's Manual



Patented **CPS®Link™** Wireless Technology

Bluetooth® **FC** **CE** **ICES-003**

OVERVIEW

The ABM EasyHood captures air speed values from air supply or return/exhaust vents in residential or commercial buildings, and easily converts that into an airflow (volume) reading. To accomplish this, the ABM EasyHood is used with an ABM-200 Airflow & Environmental Meter (or ABM-100 Airflow Meter and ABM-100 app) and a smartphone having the latest, free, CPS Link™ app installed.

KEY FEATURES

- Accurate and affordable HVAC airflow measurement
- Use smartphone and CPS Link™ app to display, store and send data (ABM-200)
- Also measures temperature, wet bulb, dew point and relative humidity (ABM-200)
- Easy operation with online guidance and visual instruction

ABM-HOOD LAYOUT



PARTS & ACCESSORIES



SPECIFICATIONS

ABM-HOOD		
Hood Opening	12" x 12" (.3 m x .3 m)	
Expansion Hood Opening	24" x 24" (.6 m x .6 m)	
Weight (with Expansion Hood)	4.75 lb (2.15 kg)	
Hood Size (with Expansion)	17.75" H x 25" W x 25" D (.45 m x .63 m x .63 m)	
ABM-HOOD-200 (when used with ABM-200 sensor)		
Wireless Connection Range	≤100 ft. (30.5 m)	
Airflow Volume (Regular Test)	0-1200 CFM (0-2,038 M³/H)	
Airflow Volume (Low Volume)	7-100 CFM (12-170 M³/H)	
Velocity (fpm)	Range: 44-12,320	Accuracy: ±0.5%
Pressure (mbar)	Range: 300-1100	Accuracy: ±0.12%
RH Range	Range: 0-85%	Accuracy: ±4%
Temperature (Range)	Range: 0 °F to 140 °F (-18 °C to 60 °C)	
	Accuracy: ±0.7 °F (0.4 °C)	
Calculates Wet Bulb	✓	
Calculates Dew Point	✓	
Bluetooth Smart	✓	
Auto Power Off	No connection or 30 sec after closing app	
Battery Type (3.0 V)	Inside ABM-200 (CR2450 Coin Cell, Lithium)	
Battery Life	> 500 hrs.	
Warranty	1 Year (including ABM-HOOD)	

APP DOWNLOAD & SETUP

For use with Apple iPhone (4S or newer), iPad (Generation 3 or newer).
All Bluetooth Smart compatible Android phones & tablets with
operating system 4.3 (Jelly Bean) or newer.

1. For ABM-200 app (CPS Link™) or ABM-100 app
go to the App Store or Google Play
2. If you have a QR code scanner app on your
phone, scan the QR code below to be
redirected to the CPS Link app download
page (App Store or Google Play).
3. After downloading app, select the
CPS Link or ABM-100 app on your
mobile device.
4. From the main screen, connect to
a. ABM_200_XXXXXX (CPS Link™)
b. or ABM_100_XXXXXX
5. For ABM-200 select ABM-EASYHOOD



CPS Link™
Download
App Now



Download on the
App Store



GET IT ON
Google Play

Version 4.3 or higher

INSTALL SENSOR

1. If using ABM-200, attach threaded mic jack metal adapter (included)
to sensor, then plug sensor into socket inside control box opening.
2. If using ABM-100, plug sensor into socket inside control box opening.

HANDS FREE MOBILE PHONE USE


1. For greater convenience, mount your
mobile phone to the adjustable
[2-3/8" to 5-5/8" (60 to 90 mm)] spring
loaded base.

*If using ABM-100, use cable inside
smartphone platform and connect to
headphone jack on smartphone.*



REGULAR TEST [0 TO 1200 CFM (0 TO 2,038 M³/H)]

1. From the ABM EasyHood screen, select **REGULAR TEST**.
2. Place hood over grille to capture airflow readings.
3. App will calculate airflow and other values.
4. When test is done, press **STOP** on mobile device screen.



ABM EasyHood Main Screen



Capture Airflow Readings



5. Press **SAVE** (or **CANCEL**) on screen to end your session.

LOW VOLUME TEST [0 TO 100 CFM (12 TO 170 M³/H)]


1. Select **LOW VOLUME** from main screen on ABM-EASYHOOD app
2. Insert low volume adapter plate into **WIDE** portion of Vortex grille (see photo below).
3. Place hood over grille to capture airflow readings
4. App will calculate airflow and other values.
- 5 When test is done, press **STOP** on mobile device screen.



ABM EasyHood Main Screen



Low volume adapter



Capture airflow readings



6. Press **SAVE** (or **CANCEL**) on screen to end your session.

EXPANSION HOOD SETUP (GRILLES UP TO 24" X 24")



TO REPLACE ABM-200 BATTERY

1. Squeeze **BOTH** sides of rubber "skin" and push **UPWARDS** simultaneously.
2. Pull "skin" over **BACK** of the housing to expose coin cell battery compartment



TRIPOD MOUNT

The EasyHood underside contains a 1/4" - 20" threaded metal fitting which may be used for attaching the EasyHood to a tripod.



WARRANTY

CPS Products, Inc. guarantees that all products are free of manufacturing and material defects to the original owner for one year from the date of purchase. If the equipment should fail during the guarantee period it will be repaired or replaced (at our option) at no charge. This guarantee does not apply to equipment that has been altered, misused or solely in need of field service maintenance. All repaired equipment will carry an independent 90 day warranty. This repair policy does not include equipment that is determined to be beyond economical repair.

Follow us on social media:



#79-114 Rev. A