

## MODEL T-620 / T-620H



**Model T-620** hydraulic pressure pump is small, lightweight and portable. The T-620 features a transparent reservoir to easy view of the test fluid. The pump is compatible with petroleum-based oils or hydraulic fluids. The reference gauge is mounted on the body manifold with a swivel fitting for easy viewing. A vernier

adjustment allows for precisely control pressure. A vent valve is provided for quick and positive shut-off and pressure release. The pump is equipped with a 24 in (60.95 cm) rubber hose with 1/4 in NPT connector and 1/4 in BSP adapter for connecting to the instrument-under-test.

### Functional specifications - Model T-620 / T-620H

Operating Pressure (Maximum)

Model T-620 ..... 200 bar / 3,000 psi

Model T-620H..... 350 bar / 5,000 psi

Wetted Parts.... Aluminum, brass, stainless steel, and Lexan®

“O” Rings ..... Buna-N

Reservoir Capacity..... 200 cl / 0.5 pint

Test medium ..... Hydraulic oil

Test Connections ..... hose 0.5 m / 20 in with 1/4” BSP

..... and NPT female terminations

Net weight ..... 0.95 kg / 2.09 lbs

### Ordering code - Model T-620 / T-620H

T-620      Hydraulic pump, 0 to 200 bar (3,000 psi)