

TECHNICAL DATA



BS-15-9C3

Features

- Camera and video functions save high resolution JPG images and record video
- Comfortable pistol grip design
- High resolution 3.2" color TFT LCD monitor
- 17mm waterproof (IP67) camera head
- Gooseneck cable retains configured shape
- Cable expandable up to 30 ft (9.1m) with extensions (optional)
- Four high visibility LED lights provide illumination in dimly lit environments
- Internal memory with option to expand (SD card sold separately)
- TV Output
- 180° mirror rotation function
- Rechargeable lithium-ion battery
- Low battery indicator and auto shut off
- Includes 17mm camera head, magnet, hook and mirror attachments, rechargeable lithium-ion battery, power supply, USB cable, video output cable and hard carrying case

Specifications

Camera

Camera Resolution:	640 x 480
Camera Diameter:	0.66" (17mm)
Viewing Distance:	5.9 to 9.8" (15 to 25cm)
Depth of Field:	10mm to infinity
Viewing Angle:	0 to 180°

General Specifications

Display:	3.2" Color TFT LCD
Display Resolution:	320 x 240
Frames per Second (FPS):	30
Standard Gooseneck/ Cable Length:	39" (1m)
Rotate Display:	Yes (180°)
Playback:	Photo and Video
Memory:	Internal / SD Card (up to 8Gb)
TV Out:	PAL / NTSC
Data Output:	USB / SD Card
LED Brightness Adjustment:	Yes (4 white LEDs)
Low Battery Indicator:	Yes
Power Supply:	Rechargeable li-ion battery
On-Screen Supported Languages:	English, Dutch, French, Spanish, Turkish
Product Certifications:	CE, IP67 (Camera Head)
Operating Temperature:	14 to 122°F (-10 to 50°C)
Storage Temperature:	14 to 140°F (-10 to 60°C)
Operating Humidity:	10 to 85%
Dimensions:	9.5 x 3.9 x 6.3" (240 x 100 x 160 mm)
Weight:	18.7oz (530g)

Model	Description
BS-150	Video Inspection Camera
SD-4GB	4GB SD Memory Card
BS-C6	6' Cable Extension
BS-15-9C3	9mm Replacement Camera Head w/ 3' Cable
BS-150/BATTERY	Replacement Battery