



## HOBO<sup>®</sup> CABLE-DR-XXX

### MX2001 Direct Read Cable

This direct read cable provides the connection between the MX2001 logger's top-end unit and water level sensor. Cables can be ordered in lengths from 0.2 to 500m for deployment in a wide range of wells. Please see specifications for pricing on the cables.

Important: The logger and sensor add 0.39 meters to the length of the cable. Cable length can vary up to 3% from the length ordered. The 5, 10, 15, 30 and 60 meter cable lengths are standard. For all cable lengths, please call for availability. For conversion tables from meters to feet and lengths of cables with the logger and sensor, please refer to our direct read cable table.



#### Key Advantages:

- Kevlar reinforced cable suspends sensor, and provides sensor communication and power
- Two o-rings in each connector ensure a long-term waterproof seal
- Cables are easy to attach or change
- Integrated strain relief provides support for long cables

## HOBO CABLE-DR-XXX Specifications

### Important information:

- The logger and sensor add 0.39 meters to the length of the cable.
- Cable length can vary up to 3% from the length ordered.

Stock Cables		
CABLE-DR-5.0	5m Direct Read Cable	\$90
CABLE-DR-010	10m Direct Read Cable	\$110
CABLE-DR-015	15m Direct Read Cable	\$130
CABLE-DR-030	30m Direct Read Cable	\$190
CABLE-DR-060	60m Direct Read Cable	\$310
Custom Cables		
CABLE-DR-xxx	xxx m Direct Read Cable	\$70 plus \$4 per meter

