

### TECHNICAL DATA



#### Features

- Compact size
- 2% basic accuracy
- Integrated banana plugs
- CE certified
- CAT. II 600V safety rating

#### Specifications

##### AC/DC Current

|                    |                                     |
|--------------------|-------------------------------------|
| Range:             | 0 to 200A                           |
| Accuracy:          | AC: $\pm(2.0\% \text{ rdg} + 0.5A)$ |
| AC Current Output: | 1mV/A                               |

##### General Specifications

|                         |                                       |
|-------------------------|---------------------------------------|
| Jaw Opening:            | 0.62" (16mm)                          |
| Overvoltage Category:   | CAT. II 600V, CAT.III 300V            |
| Product Certifications: | CE                                    |
| Operating Temperature:  | 32 to 122°F (0 to 50°C)               |
| Storage Temperature:    | 14 to 122°F (-10 to 50°C)             |
| Dimensions:             | 4.4 x 2.0 x 1.3"<br>(111 x 50 x 33mm) |
| Weight:                 | 4.6oz (129g)                          |

| Model      | Description                     |
|------------|---------------------------------|
| CP-09      | AC Current Adapter, 200A        |
| CA-52A     | Soft Carrying Case              |
| CP-09-NIST | AC Current Adapter, 200A & NIST |