



InTemp® CX702 Data Logger

Cryogenic Logger - Single Use

The InTemp CX702 Cryogenic data logger is a low-cost Bluetooth Low Energy (BLE)-enabled single-use logger that records temperature data for up to 90 days. The CX702's built-in 1.5m probe measures temperatures as low as -200°C (-328°F) and includes a protective sheath to prevent accidental cutting of the cable.

Using the InTemp® app on your mobile device, you can easily configure the CX702 with one of multiple preset configurations, or set up a custom configuration. The logger has a built-in alarm to alert you to excursions. And logger reports can be quickly downloaded to your phone or tablet and uploaded to an InTempConnect® account, where you can analyze and export data as needed.

With the optional CX Gateway, you can get real-time notification of temperature excursions and automatically download data from loggers within range of the device. Learn more about the CX Gateway here.



Key Advantages:

- Single-Point ILAC/ISO17025 NIST Certificate of Calibration, valid for one year from date of purchase
- IATA Battery compliant
- Record up to 14,000 data points
- Anti-cut sheath
- Integrates with mobile and cloud platforms for a 21 CFR Part 11 compliant solution
- Compact and lightweight – ideal for shipping pharmaceuticals
- No need to open containers to access data
- Ensures secure data via encrypted technology

InTemp CX702 Data Logger Specifications

Temperature Probe

Sensor Range	-200° to 50°C (-328° to 122°F); To ensure insulation integrity, avoid flexing the wire during exposure to temperatures below -100°C (-148°F)
Accuracy	±1.5°C from -200° to -90°C (±2.7°F from -328° to -130°F) ±1.0°C from -90° to -10°C (±1.8°F from -328° to 14°F) ±0.5°C from -10° to 50°C (±0.9°F from 14° to 122°F)

Resolution	0.013°C at 25°C (0.023°F at 77°F)
-------------------	-----------------------------------

NIST Calibration	CX702 and CX703: Single-point NIST calibration, probe only CX703-UN: Calibration not included
-------------------------	--------------------------------------------------------------------------------------------------

Cable Length	1.5 m (4.92 ft)
---------------------	-----------------

Probe Dimensions	Food-grade stainless steel probe with blunt tip, 31.75 mm (1.25 inches) long, 4.78 mm (0.188 inches) diameter
-------------------------	---------------------------------------------------------------------------------------------------------------

Logger

Logger Operating Range	-30° to 50°C (-22° to 122°F)
-------------------------------	------------------------------

Radio Power	1 mW (0 dBm)
--------------------	--------------

Transmission Range	Approximately 30.5 m (100 ft) line-of-sight
---------------------------	---------------------------------------------

Wireless Data Standard	Bluetooth Low Energy (Bluetooth Smart)
-------------------------------	----------------------------------------

Type	Single use
-------------	------------

Duration	90 days
-----------------	---------

Shelf Life	Up to 1 year
-------------------	--------------

Logging Rate	1 second to 18 hours
---------------------	----------------------

Battery	CR2450 3V lithium, not replaceable. Battery for CX602 and CX702 models lasts for duration specified when logger is used within the 1-year shelf life. Battery life for the CX603 and CX703 models is 1 year, typical with logging interval of 1 minute. Faster logging intervals, remaining connected with the InTemp app, excessive downloads, and paging may impact battery life.
----------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Memory	16,000 measurements
---------------	---------------------

Full Memory Download Time	Approximately 30 seconds; may take longer the farther the device is from the logger
----------------------------------	-------------------------------------------------------------------------------------

Dimensions	6.9 x 4.5 x 1.1 cm (2.71 x 1.76 x 0.42 inches)
-------------------	------------------------------------------------

Weight	25.5 g (0.90 oz)
---------------	------------------

Environmental Rating	IP65
-----------------------------	------

CE	The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).
-----------	--------------------------------------------------------------------------------------------------------------

Passed RTCA DO160G, part 21H